# **COSMIC ELITE 11**

Use: for road bike use only. Any other use (such as on a tandem, cyclo-cross bike, or off-road use...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg.

#### WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front 815 g Rear M10 Rear ED11

#### WHEEL REFERENCES

Front 112 108 10 Rear M10 112 109 11 Rear ED11 112 110 12 Pair M10 112 111 14 112 112 14 Pair ED11

#### **RIMS**

SALES REFERENCES:

Front and Rear: 120 173 15



#### Ø VALVE HOLE

Ø: 6.5 mm Length: ≥ 55 mm





#### RECOMMENDED TIRE WIDTH

Dimensions: ETRTO 622 x 15C Recommended tire width: 19 to 32 mm

#### **HUBS**

MAINTENANCE: Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.





#### WHEEL BUILDING

REFERENCES AND

LENGTHS:

Drive side:

Non-drive side:

120 289 01, length 276 mm (per 10 with nipples and 1 retaining ring)

120 291 01, length 292 mm (per 10, with nipples)

120 290 01, length 276 mm (per 10 with nipples and 1 retaining ring)

# FEATURES:

Rear Wheel: black steel bladed, straight pull spokes with ABS spoke nipples

Front Wheel: Self-Lock type black steel bladed, straight pull spokes with standard nipples

# LACING PATTERN:

Front: radial

Rear: 2-crossed drive side, radial non-drive side

# TENSION:

Front: 70 to 90 kg

Rear drive side: 145 to 165 kg

## **ACCESSORIES**

## WHEELS SUPPLIED WITH:

- Conventional alu quick-release skewer on front M40350
- Conventional alu quick-release skewer on rear M40351
- Rim tape
- Aerodynamic spoke wrench M40567 (with rear wheel)
- Aluminum valve extender, 60 mm, 118 952 01
- ED11 12D locking ring (with rear wheel ED11) 108 317 01
- · Wheel user guide

## **MAINTENANCE**

Replacing the front axle and bearings Replacing the rear axle

Maintaining and replacing the free wheel mechanism

Replacing the rear bearings

Replacing a spoke

Replacing the front rim Replacing the rear rim

See 2004 TM, page 19 See 2004 TM, page 20 See 2004 TM, page 21

See 2002 TM, page 22 See 2008 TM, page 25

See 2008 TM, page 25 See 2010 TM, page 22

Refer to the website for quick and convenient access to information: www.tech-mavic.com