

CROSSRIDE DISC 11 INTL



Use: use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.
Recommended maximum weight of the cyclist and equipment: 85 kg.

WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER AND WITHOUT ADAPTER

Front: 880 g
Rear: 1020 g

WHEEL REFERENCES

STANDARD INT

Front: 127 091 10
Rear: 127 092 13
Pair: 127 093 14

| RIMS | SALES REFERENCES: Front and rear: 120 216 15 | |
|------|--|--|
| | <p>Ø VALVE HOLE Ø: 8.5 mm with 6.5 mm valve adapter Length: ≥ 32 mm</p> | <p>RECOMMENDED TIRE WIDTH AND PRESSURE Dimensions: Ø 26" ETRTO 559 x 19C Recommended tire width: 1.5 to 2.3</p> |
| | | |

| HUBS | MAINTENANCE: Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer. | |
|------|---|--|
| | | |
| | | |

| WHEEL BUILDING | REFERENCES AND LENGTHS: | Front and rear: 996 875 01, length 261 mm (per 12, with nipples) |
|---|--|--|
| <p>FEATURES: Black steel straight pull spokes with Self-Lock system and conventional spoke nipples</p> | <p>LACING PATTERN: Front and rear: 2-cross lacing on both sides</p> | <p>TENSION: Front: 100 to 120 kg Rear drive side: 120 to 140 kg</p> |

| ACCESSORIES | WHEELS SUPPLIED WITH: | MAINTENANCE |
|--|-----------------------|---|
| <ul style="list-style-type: none"> • BR 101 front quick release: M40350 • BR 101 rear quick release: M40351 • Rim tape 559x20x0.6 • Wheel user guide | | <p>Replacing the front axle and bearings See 2004 TM, page 19 Replacing the rear axle See 2004 TM, page 20 Maintaining and replacing the free wheel mechanism See 2004 TM, page 21 Replacing the rear bearings See 2004 TM, page 22 Replacing a spoke See 2004 TM, page 25 Replacing the front rim See 2009 TM, page 38 Replacing the rear rim See 2009 TM, page 39</p> |
| <p>Refer to the website for quick and convenient access to information: www.tech-mavic.com</p> | | |



CROSSRIDE DISC 11 CL

Use: use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.
Recommended maximum weight of the cyclist and equipment: 85 kg.

WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER AND WITHOUT ADAPTER

Front: 880 g
Rear: 1020 g

WHEEL REFERENCES

CENTER LOCK

Front: 127 088 10
Rear: 127 089 13
Pair: 127 090 14

| RIMS | SALES REFERENCES: Front and rear: 120 216 15 | |
|------|--|--|
| | <p>Ø VALVE HOLE Ø: 8.5 mm with 6.5 mm valve adapter Length: ≥ 32 mm</p> | <p>RECOMMENDED TIRE WIDTH AND PRESSURE Dimensions: Ø 26" ETRTO 559 x 19C Recommended tire width: 1.5 to 2.3</p> |
| | | |

| HUBS | MAINTENANCE: Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer. | |
|------|---|--|
| | | |
| | | |

| WHEEL BUILDING | REFERENCES AND LENGTHS: | Front and rear: 996 875 01, length 261 mm (per 12, with nipples) |
|---|--|---|
| FEATURES: Black steel straight pull spokes with Self-Lock system and conventional spoke nipples | LACING PATTERN: Front and rear: 2-cross lacing on both sides | TENSION: Front: 100 to 120 kg Rear drive side: 120 to 140 kg |

| ACCESSORIES | WHEELS SUPPLIED WITH: | MAINTENANCE |
|--|-----------------------|---|
| <ul style="list-style-type: none"> • BR 101 front quick release: M40350 • BR 101 rear quick release: M40351 • Rim tape 559x20x0.6 • Wheel user guide | | Replacing the front axle and bearings Replacing the rear axle Maintaining and replacing the free wheel mechanism Replacing the rear bearings Replacing a spoke Replacing the front rim Replacing the rear rim |
| | | See 2004 TM, page 19 See 2004 TM, page 20 See 2004 TM, page 21 See 2004 TM, page 22 See 2004 TM, page 25 See 2009 TM, page 38 See 2009 TM, page 39 |
| Refer to the website for quick and convenient access to information: www.tech-mavic.com | | |