

CROSSTRAIL



Use: use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg

WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front: 760 g
Rear: 890 g

REFERENCES

Front: 325 516 10
Rear: 325 517 13
Pair: 325 570 14

RIMS	SALES REFERENCES
	<p>Front and Rear: 351 180 15 Same as ST 12</p>
	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>Ø VALVE HOLE Ø: 6.5 mm Length: ≥ 32 mm</p> </div> <div style="width: 45%;"> <p>RECOMMENDED TYRE WIDTH Dimensions: Ø 26" ETRTO 559 x 19C and Tubeless UST compatible. Recommended clincher width: 1.5" to 2.3"</p> </div> </div> <p>When replacing the front rim: 1. With the valve hole near you, the raised indicator bump must be to the right of the valve hole. 2. The spoke in the first hole to the right of the valve hole is a non-braking spoke and should be inserted in the disc side.</p> <p>When replacing the rear rim: 1. With the valve hole near you, the two raised indicator bumps must be to the right of the valve hole. 2. The spoke in the first hole to the right of the valve hole is a non-traction spoke and should be inserted in the drive side.</p>

HUBS	MAINTENANCE:
	Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.

WHEEL BUILDING	REFERENCES AND LENGTHS	Front and rear non-drive side:	120 341 01, length 267.5 mm (per 12, integrated nipples)
		Rear drive side:	120 342 01, length 265 mm (per 12, integrated nipples)

FEATURES:

Black, flat, straight pull steel spokes with integrated and self-locking M7 aluminum spoke nipples

LACING PATTERN:

Front and rear: 2-cross lacing on both sides

TENSION:

Front: 100 to 120 kg
Rear drive side: 115 to 135 kg

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> • BX 301 rear quick-release skewer M40352 • 2 Removable round UST valves 129 838 01 • Rear Adapters 12x142 mm 329 650 01 • Rear Adapters 12=>9.5 mm 308 731 01 • Multifunction adjustment wrench 325 423 01 • User guides 		<p>Specific tool:</p> <ul style="list-style-type: none"> • Front bearing: 108 850 01 & 996 887 01 • Rear bearing: M40119 • Spoke wrench: 996 079 01
OPTIONS	<p>Front Adapters 9 mm + quick-release skewer: 996 941 01</p>	<p>Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) www.tech-mavic.com</p>