

# CROSSRIDE DISC 9 mm



**Use:** use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg

## WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front: 880 g  
Rear: 1020 g

## REFERENCES

Front: 326 554 10  
Rear: 326 555 13  
Pair: 326 556 14

RIMS	SALES REFERENCES	Front and rear: 351 240 15
	<p><b>Ø VALVE HOLE</b> Ø: 8.5 mm Length: ≥ 32 mm</p>	<p><b>RECOMMENDED TYRE WIDTH</b> Dimensions: Ø 26" ETRTO 559 x 19C compatible Recommended clincher width: 1.5" to 2.3"</p>

HUBS	MAINTENANCE: Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.

WHEEL BUILDING	REFERENCES AND LENGTHS	Front and rear: 996 875 01, length 261 mm (per 14, with nipples)
<p><b>FEATURES:</b> Black, round, straight pull steel spokes with Self Lock system and conventional spoke nipples</p>	<p><b>LACING PATTERN:</b> Front and rear: 2-cross lacing on both sides</p>	<p><b>TENSION:</b> Front: 100 to 120 kg Rear drive side: 115 to 125 kg</p>

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> <li>Conventional aluminum quick-release skewer on front M40350</li> <li>Conventional aluminum quick-release skewer on rear M40352</li> <li>Rim tape 20x559 (1 per wheel)</li> <li>User guide</li> </ul>		<p><b>Specific tool:</b></p> <ul style="list-style-type: none"> <li>Front bearing: M40119 &amp; M40373</li> <li>Rear bearing: M40119 &amp; M40373</li> </ul>
<p>Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) <a href="http://www.tech-mavic.com">www.tech-mavic.com</a></p>		

# CROSSRIDE DISC 9 MM *Center-Lock*



**Use:** use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg

## WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front: 880 g  
Rear: 1020 g

## REFERENCES

Front: 326 563 10  
Rear: 326 564 13  
Pair: 326 565 14

RIMS	SALES REFERENCES	Front and rear: 351 240 15
	<p><b>Ø VALVE HOLE</b> Ø: 8.5 mm Length: ≥ 32 mm</p>	<p><b>RECOMMENDED TYRE WIDTH</b> Dimensions: Ø 26" ETRTO 559 x 19C compatible Recommended clincher width: 1.5" to 2.3"</p>

HUBS	<b>MAINTENANCE:</b> Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.	

WHEEL BUILDING	REFERENCES AND LENGTHS	Front and rear: 996 875 01, length 261 mm (per 14, with nipples)
<b>FEATURES:</b> Black, round, straight pull steel spokes with Self Lock system and conventional spoke nipples	<b>LACING PATTERN:</b> Front and rear: 2-cross lacing on both sides	<b>TENSION:</b> Front: 100 to 120 kg Rear drive side: 115 to 125 kg

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> <li>Conventional aluminum quick-release skewer on front M40350</li> <li>Conventional aluminum quick-release skewer on rear M40352</li> <li>Rim tape 20x559 (1 per wheel)</li> <li>User guide</li> </ul>		<p><b>Specific tool:</b></p> <ul style="list-style-type: none"> <li>Front bearing: M40119 &amp; M40373</li> <li>Rear bearing: M40119 &amp; M40373</li> </ul>
<p>Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) <a href="http://www.tech-mavic.com">www.tech-mavic.com</a></p>		