




# TECHNICAL FEATURES OF THE NEW 2007 RIMS

		MTB	
		CROSS MOUNTAIN	ENDURO FR
		XM 719 DISC	EN 321 DISC
<b>RIM WIDTH</b>			
<b>Technologies</b>			
<b>Material</b>		MAXTAL	6106
<b>Valve hole diameter (in mm)</b>		8.5 supplied with valve adapter	8.5 supplied with valve adapter
<b>ETRTO compatibility</b>		559 x 19	559 x 21
<b>Recommended tire width (in mm)</b>		1.5 to 2.3	2.1 to 2.5
<b>Eyelets</b>		Simple	Simple
<b>Average weight (in grams)</b>		460	570
<b>Finish and drilling</b>	<b>Black 32-hole</b>	995 003 32	995 008 32
	<b>Black 36-hole</b>	995 003 36	995 008 36
<b>Recommended spoke nipple length (in mm)</b>		12	12
<b>Spoke support diameter (in mm)</b>		536	536
<b>Recommended rim tape (ETRTO x length x thickness)</b>		559 x 20 x 0.6	559 x 23 x 0.6

Mavic rims not appearing in the above chart have not been changed. Their technical features can be found in the technical manuals from previous years or on the technical manual website: [www.tech-mavic.com](http://www.tech-mavic.com).