

# DEEMAX ULTIMATE + REAR 12x150



**Use:** use only on a MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 115 kg.

## WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front: 910 g  
Rear 9/12x135: 1,055 g  
Rear 12x150: 1,065 g

## WHEEL REFERENCES

Front: 129 521 10  
Rear 9/12x135: 128 081 13  
Rear 12x150: 129 522 13  
Pair 9/12x135: 128 082 14  
Pair 12x150: 129 523 14

RIMS	SALES REFERENCES	Front: 996 919 10 Rear: 996 919 13
	<b>Ø VALVE HOLE</b> Ø: 6.5 mm Length: ≥ 32 mm	<b>RECOMMENDED TYRE WIDTH</b> Dimensions: Ø 26" ETRTO 559 x 21C compatible and Tubeless UST. Recommended tyre width: 2.1" to 2.5".
	<b>When replacing the front rim:</b> 1. With the valve hole near you, the raised indicator bump must be to the <b>left</b> of the valve hole. 2. The spoke in the first hole to the right of the valve hole is a non-braking spoke and should be introduced into the disc side. <b>When replacing the rear rim:</b> 1. With the valve hole near you, the two raised indicator bumps must be to the <b>right</b> of the valve hole. 2. The spoke in the first hole to the right of the valve hole is a non-traction spoke and should be inserted in the drive side.	

HUBS	MAINTENANCE:
	Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.

WHEEL BUILDING	REFERENCES AND LENGTHS	Front: 308 638 01, length 271 mm (per 14, integrated nipples) Rear drive side: 308 639 01, length 266 mm (per 16, integrated nipples) Rear non-drive side: 308 640 01, length 268 mm (per 16, integrated nipples)
<b>FEATURES:</b> Black stainless steel flat straight pull spokes with integrated, self-locking M7 aluminum spoke nipples	<b>LACING PATTERN:</b> Front and rear: 3-cross lacing on both sides	<b>TENSION:</b> Front disc side: 100 to 120 kg Rear drive side: 110 to 130 kg

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> <li>• BX 601 rear quick-release M40141 (with 135 mm rear wheel)</li> <li>• 2 Removable UST valves 995 282 01</li> <li>• Adapters 20 mm 129 829 01 (mounted on front wheel)</li> <li>• Adapters 12x142 mm 308 593 01 (with 135 mm rear wheel)</li> <li>• Axle reducers 12⇒9.5 mm 308 731 01 (with 135 mm rear wheel)</li> <li>• 2 multifunction adjustment wrenches 325 423 01</li> <li>• User guide</li> </ul>		Replacing the front axle and bearings Replacing the rear axle and bearings Maintaining and replacing the free wheel mechanism Replacing a spoke Replacing the front rim Replacing the rear rim  See 2003 TM, page 19 See 2012 TM, page 20 See 2009 TM, page 29 See 2009 TM, page 41 See 2009 TM, page 42/43 See 2009 TM, page 44/45
Refer to the website for quick and convenient access to information: <a href="http://www.tech-mavic.com">www.tech-mavic.com</a>		