

# KSYRIUM SLS (clincher version)

**Use:** for road bike or cyclo-cross bike use only. Any other use (such as on a tandem or off-road bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg.

## WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER AND WITHOUT CLINCHER

Front	605 g
Rear M10	805 g
Rear ED11	790 g

## WHEEL REFERENCES

Front	325 691 10
Rear M10	325 692 11
Rear ED11	325 693 12
Pair M10	325 694 14
Pair ED11	325 695 14

RIMS	SALES REFERENCES	Front: 330 001 10 Rear: 330 001 13
	<b>Ø VALVE HOLE</b> Ø: 6.5 mm	<b>RECOMMENDED TYRE WIDTH</b> Dimensions: 622x15C Recommended clincher width: 23 to 32 mm
	<b>When replacing the rear rim:</b> 1. With the valve hole near you, the two raised indicator bumps must be to the right of the valve hole. 2. The spoke in the first hole to the right of the valve hole should be inserted in the drive side.	

HUBS	<b>MAINTENANCE:</b> Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.	

WHEEL BUILDING	REFERENCES AND LENGTHS:	Front: 330 003 01, length 283.5 mm (per 10, integrated nipples) Drive side: 120 303 01, length 275 mm (per 10 decorated, integrated nipples) Non-drive side: 120 304 01, length 298.5 mm (per 10, integrated nipples)
<b>FEATURES:</b>	Front: black swaged, bladed, straight pull Zicral spokes with integrated and self-locking M7 nipples Rear: black bladed, straight pull Zicral spokes with integrated and self-locking M7 nipples	<b>LACING PATTERN:</b> Front: radial Rear: Isopulse
		<b>TENSION:</b> Front: 85 to 95 kg Rear drive side: 115 to 135 kg

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> <li>• BR 601 front quick-release skewer M40149</li> <li>• BR 601 rear quick-release skewer M40150</li> <li>• Removable computer magnet M40540 (with front wheel)</li> <li>• 2 multifunction adjustment wrenches 325 423 01</li> <li>• ED11 12D locking ring (with rear wheel ED11) 108 317 01</li> <li>• Yksion Pro White Griplink 23 mm front clincher (328 351 23)</li> <li>• Yksion Pro White PowerLink 23 mm rear clincher (328 352 23)</li> <li>• Mavic butyl inner tubes (127 385 01)</li> <li>• Wheel and clincher user guide</li> </ul>		<b>Specific tool:</b> <ul style="list-style-type: none"> <li>• Front bearing: M40120</li> <li>• Rear bearing: M40120 and 351 266 01</li> <li>• Spoke wrench: 996 079 01</li> </ul>
Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) <a href="http://www.tech-mavic.com">www.tech-mavic.com</a>		