

CROSSMAX ENDURO WTS 26



Use: use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg.

WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER AND WITHOUT TYRE

Front: 825 g
Rear: 835 g

REFERENCES

Front: 355 217 10
Rear: 355 218 13
Pair: 355 219 14

RIMS	SALES REFERENCES
	Front: 366 460 10 Rear: 366 467 13
	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>Ø VALVE HOLE Ø: 6.5 mm</p> </div> <div style="width: 45%;"> <p>RECOMMENDED TYRE WIDTH Dimensions: Front ETRTO 559x21C and Rear ETRTO 559x19C Recommended clincher width: Front: 2.1" to 2.5" Rear: 1.5" to 2.3"</p> </div> </div>
	<p>When replacing the front rim:</p> <ol style="list-style-type: none"> With the valve hole near you, the raised indicator bump must be to the right of the valve hole. The spoke in the first hole to the right of the valve hole is a non-braking spoke and should be inserted in the disc side. <p>When replacing the rear rim:</p> <ol style="list-style-type: none"> With the valve hole near you, the two raised indicator bumps must be to the right of the valve hole. The spoke in the first hole to the right of the valve hole should be introduced into the drive side in a hole marked on the hub.

HUBS	MAINTENANCE:
	Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.

WHEEL BUILDING	REFERENCES AND LENGTHS:	FRONT:	DRIVE SIDE:	NON-DRIVE SIDE:
		366 468 01, length 261.5 mm (per 11 + 1 decorated, integrated nipples)	366 472 01, length 239 mm (per 9 + 1 decorated, integrated nipples)	366 471 01, length 269 mm (per 10, integrated nipples)
FEATURES:	Bladed, straight pull Zircal spokes with integrated aluminum Fore nipples			
	LACING PATTERN:	Front: 2-cross lacing on both sides Rear: Isopulse		
	TENSION:	Front: 105 to 125 kg Rear drive side: 105 to 125 kg		

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> BX 601 rear quick-release M40141 2 Removable round UST valves 129 838 01 Front Adapters 15 mm 129 828 01 Front Adapters 20mm 129 829 01 Rear Adapter 12=>9.5 mm 308 731 01 Rear Adapters 12x142 mm 308 593 01 Multifunction adjustment wrench 325 423 01 Crossmax Charge front clincher 26x2.40 (356 296 24) Crossmax Roam XL rear clincher 26x2.30 (356 297 23) 2 sets of specific disc screws (6 screws per set) 308 719 01 User manual Sheet of Mavic stickers 		Specific tool: <ul style="list-style-type: none"> Front bearing: M40119 & M40218 Rear bearing: M40119 Spoke wrench: 996 079 01
OPTIONS	<ul style="list-style-type: none"> Front Adapters 9 mm + quick-release skewer: 129 827 01 	Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) www.tech-mavic.com