

CROSSMAX SLR 650b (27.5) Lefty



Use: use only on a Cross-country or Cross-mountain MTB fitted with disc brakes.
Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg.

WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front: 710 g
Rear: 830 g

CANNONDALE OEM

RIMS	SALES REFERENCES
	Front: 366 925 10 Rear: 366 926 13
	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>Ø VALVE HOLE Ø: 6.5 mm</p> </div> <div style="width: 45%;"> <p>RECOMMENDED TYRE WIDTH Dimensions: ETRTO 584x19C Recommended clincher width: 1.5" to 2.3"</p> </div> </div> <p>When replacing the front rim:</p> <ol style="list-style-type: none"> With the valve hole near you, the raised indicator bump must be to the right of the valve hole. The spoke in the first hole to the right of the valve hole is a non-braking spoke and should be inserted in the disc side. <p>When replacing the rear rim:</p> <ol style="list-style-type: none"> With the valve hole near you, the two raised indicator bumps must be to the right of the valve hole. The spoke in the first hole to the right of the valve hole should be introduced into the drive side in a hole marked on the hub.

HUBS	MAINTENANCE:
	Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.

WHEEL BUILDING	REFERENCES AND LENGTHS:
	Front: 366 749 01, length 274 mm (per 10+1 decorated, integrated nipples) Non-drive side: 366 750 01, length 281.5 mm (per 10 + 1 decorated, integrated nipples) Drive side: 366 751 01, length 251.5 mm (per 10 + 1 decorated, integrated nipples)
FEATURES: Black, bladed, straight pull Zircal spokes with integrated aluminum Fore nipples	LACING PATTERN: Front: 2-cross lacing on both sides Rear: Isopulse
	TENSION: Front: 105 to 115 kg Rear drive side: 105 to 115 kg

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> • BX 601 rear quick-release M40141 • Mavic wheel bags 857 144 01 • 2 Removable round UST valves 129 838 01 • Rear Adapter 12=>9.5 mm 308 731 01 • Rear Adapters 12x142 mm 308 593 01 • Computer magnet M40540 (with front wheel) • Multifunction adjustment wrench 325 423 01 • Lefty assembly accessories M40777 • 2 sets of specific disc screws (6 screws per set) 308 719 01 • User manual • Sheet of Mavic stickers 		<p>Specific tool:</p> <ul style="list-style-type: none"> • Front bearing: 996 887 01 & M40218 • Rear bearing: M40119 • Spoke wrench: 996 079 01 <p>Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) www.tech-mavic.com</p>