

# CROSSONE 26 / 650b / 29 15 mm



**Use:** use only on a Cross-country or Cross-mountain MTB fitted with disc brakes.  
Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg.

## WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

**26"':** Front: 850 g  
Rear: 1035 g  
**650b:** Front: 905 g  
Rear: 1090 g  
**29"':** Front: 950 g  
Rear: 1135 g

## REFERENCES

**26"':** Front: 356 629 10  
Pair: 356 638 14  
**650b:** Front: 356 632 10  
Pair: 356 641 14  
**29"':** Front: 356 635 10  
Pair: 356 644 14

RIMS	SALES REFERENCES 26"': Front and rear: 366 930 15 / 650b: Front and rear: 366 931 15 / 29"': Front and rear: 366 932 15	
	<p><b>Ø VALVE HOLE</b> Ø: 8.5 mm</p>	<p><b>RECOMMENDED TYRE WIDTH</b> Dimensions: <b>26"':</b> ETRTO 559x19C <b>650b:</b> ETRTO 584x19C <b>29"':</b> ETRTO 622x19C Recommended clincher width: 1.5" to 2.3"</p>

HUBS	MAINTENANCE: Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.	

WHEEL BUILDING	REFERENCES AND LENGTHS:	26"': Front and rear non-drive side: 366 898 01, length 264 mm (per 12, nipples included) Rear drive side: 366 900 01, length 262 mm (per 12, nipples included)
		650b: Front and rear non-drive side: 366 901 01, length 278 mm (per 12, nipples included) Rear drive side: 366 902 01, length 276 mm (per 12, nipples included)
		29"': Front and rear non-drive side: 366 903 01, length 296 mm (per 12, nipples included) Rear drive side: 366 904 01, length 294 mm (per 12, nipples included)
<b>FEATURES:</b>	Black, round, straight pull steel spokes with steel ABS type spoke nipples	<b>LACING PATTERN:</b> Front and rear: 2-cross lacing on both sides
		<b>TENSION:</b> Front: 100 to 120 kg Rear drive side: 115 to 125 kg
ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> <li>BR 101 rear quick-release skewer M40351</li> <li>Rim strip (1 per wheel): <b>26"':</b> 20x559 <b>650b:</b> 20x584 <b>29"':</b> 20x622</li> <li>Valve reduction M40381</li> <li>User manual</li> </ul>		Specific tool: <ul style="list-style-type: none"> <li>Front bearing: 108 850 01 &amp; 996 887 01</li> <li>Rear bearing: M40119 &amp; M40373</li> </ul>
OPTIONS	<ul style="list-style-type: none"> <li>Front Adapters 9 mm + quick-release skewer: 996 941 01</li> </ul>	Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) <a href="http://www.tech-mavic.com">www.tech-mavic.com</a>