

# CROSSONE 26 / 650b / 29 9 mm



**Use:** use only on a Cross-country or Cross-mountain MTB fitted with disc brakes.  
Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg.

## WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

<b>26"</b> :	Front:	850 g
	Rear:	1035 g
<b>650b</b> :	Front:	905 g
	Rear:	1090 g
<b>29"</b> :	Front:	950 g
	Rear:	1135 g

## REFERENCES

<b>26"</b> :	Front / Rear:	354 034 10 / 354 035 13
	Pair:	354 036 14
<b>650b</b> :	Front / Rear:	356 072 10 / 356 073 13
	Pair:	356 074 14
<b>29"</b> :	Front / Rear:	354 024 10 / 354 025 13
	Pair:	354 026 14

RIMS	SALES REFERENCES	<b>26"</b> : Front and rear: 366 930 15 / <b>650b</b> : Front and rear: 366 931 15 / <b>29"</b> : Front and rear: 366 932 15	
	<p><b>Ø VALVE HOLE</b> Ø: 8.5 mm</p>	<p><b>RECOMMENDED TYRE WIDTH</b> Dimensions: <b>26"</b>: ETRTO 559x19C <b>650b</b>: ETRTO 584x19C <b>29"</b>: ETRTO 622x19C Recommended clincher width: 1.5" to 2.3"</p>	

HUBS	<b>MAINTENANCE:</b> Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.		

WHEEL BUILDING	REFERENCES AND LENGTHS:	<b>26"</b> : Front and rear non-drive side: 366 898 01, length 264 mm (per 12, nipples included) Rear drive side: 366 900 01, length 262 mm (per 12, nipples included)	
		<b>650b</b> : Front and rear non-drive side: 366 901 01, length 278 mm (per 12, nipples included) Rear drive side: 366 902 01, length 276 mm (per 12, nipples included)	
		<b>29"</b> : Front and rear non-drive side: 366 903 01, length 296 mm (per 12, nipples included) Rear drive side: 366 904 01, length 294 mm (per 12, nipples included)	
<b>FEATURES:</b>	Black, round, straight pull steel spokes with steel ABS type spoke nipples	<b>LACING PATTERN:</b>	Front and rear: 2-cross lacing on both sides
		<b>TENSION:</b>	Front: 100 to 120 kg Rear drive side: 115 to 125 kg

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> <li>BR 101 front quick-release skewer M40350</li> <li>BR 101 rear quick-release skewer M40351</li> <li>Rim strip (1 per wheel): <b>26"</b>: 20x559 <b>650b</b>: 20x584 <b>29"</b>: 20x622</li> <li>Valve reduction M40381</li> <li>User manual</li> </ul>		<p>Specific tool:</p> <ul style="list-style-type: none"> <li>Front bearing: M40119 &amp; M40373</li> <li>Rear bearing: M40119 &amp; M40373</li> </ul> <p>Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) <a href="http://www.tech-mavic.com">www.tech-mavic.com</a></p>