

CROSSRIDE DISC 650b (27.5)



Use: use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 100 kg.

WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front: 905 g
Rear: 1020 g

REFERENCES

Front: 356 057 10
Rear: 356 058 13
Pair: 356 059 14

RIMS	SALES REFERENCES Front and rear: 366 933 15	
	<p>Ø VALVE HOLE Ø: 8.5 mm</p>	<p>RECOMMENDED TYRE WIDTH Dimensions: ETRTO 584x19C Recommended clincher width: 1.5" to 2.3"</p>

HUBS	MAINTENANCE: Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.	

WHEEL BUILDING	REFERENCES AND LENGTHS:	FRONT AND REAR NON-DRIVE SIDE: 366 915 01, length 277 mm (per 12, nipples included)	REAR DRIVE SIDE: 366 916 01, length 275 mm (per 12, nipples included)
FEATURES: Black, bladed, straight pull steel spokes with steel ABS type spoke nipples	LACING PATTERN: Front and rear: 2-cross lacing on both sides	TENSION: Front: 100 to 120 kg Rear drive side: 115 to 125 kg	

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> Rim strip 20x584 (1 per wheel) Rear Adapters 12x142 mm: 329 650 01 Valve reduction M40381 User manual 		Specific tool: <ul style="list-style-type: none"> Front bearing: 108 850 01 & 996 887 01 Rear bearing: M40119
OPTIONS	Front Adapters 9 mm + quick-release skewer: 996 941 01 Rear Adapters 9x135 mm + quick-release skewer: 308 731 01	Refer to the website for quick and convenient access to maintenance information (replacement of an axle, bearings, free wheel, spokes, and rims) www.tech-mavic.com