







## FEATURES OF THE NEW 2014 RIMS

		MTB Fast & Light			MTB Tough & Dynamic		
		XM 319 DISC 650b / 27.5	XM 819 DISC	XM 819 DISC 29	EN 321 DISC 650b / 27.5	EN 821 DISC	EN 821 DISC 29
Rim cross section							
Material		6106	Maxtal	Maxtal	6106	Maxtal	Maxtal
Valve hole diameter (in mm)		8.5 including valve adapter	6.5	6.5	8.5 including valve adapter	6.5	6.5
ETRTO compatibility		584x19	559x19	622x19	584x21	559x21	622x21
Recommended tyre width (in inches)		1,5 to 2,3	1,5 to 2,3	1,5 to 2,3	2,0 to 2,5	2,0 to 2,5	2,0 to 2,5
Eyelets		simple	Fore	Fore	simple	Fore	Fore
Nominal weight (in grams)		535	405	450	590	460	505
Finish and drilling	<i>Noir 32 trous</i>	355 455 32	355 450 32	355 451 32	355 461 32	355 459 32	355 460 32
	<i>Black 36 holes</i>	355 455 36			355 461 36		
Recommended spoke nipple length (in mm)		12	-	-	12	-	-
Spoke support diameter (in mm)		556.5	532	594.5	560.4	532	594.5
Recommended rim strip (ETRTO x width x thickness)		584 x 20 x 0,6	-	-	584 x 20 x 0,6	-	-

## MOUNTING OF THE NEW 2014 RIMS: XM 819 / XM 819 29"/ EN 821 / EN 821 29"

These high-end rims have an asymmetrical profile for better balance of spoke tension and ensure better rim and wheel ageing.

Care must thus be taken to ensure proper rim fitting direction.

A sticker placed on the weld (opposite the valve) indicates the rotation direction for front or rear mounting:

