MAVIC E-CROSSMAX XLR 29

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Minimum tyre size: width 52mm - pressure max. 2.35Bar/34PSI
Non-Boost : 15 to 9mm front adapter for quick release ([99694101])

REFERENCES WHEELS

Jante avant E-Crosstrail Carbone SL



Specifications	Maxi target
Frontal run out	0,5mm
Lateral run out	0,5mm
Centrering	1,0mm (2x0,5)
Tension daN Disc side	81 > 107

RIMS

 :

1	V00101631	KIT FT/RR RIM E XTRAIL SL CARB

SPOKES

2	V00101731	KIT 14 BTD SPK298 EXTRAIL SL C

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019
7	N/A	HUB BODY
8	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL

ADAPTERS

6	V2372501	15mm MTB Axle Cap QRM Auto From 2019

MAVIC E-CROSSMAX XLR 29

DELIVERED WITH

User guide	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	
Pre-installed tubeless rim tape	
UST valve and accessories (129 838 01)	
2 replacement spokes with each wheel	
12 to 9mm rear adapter for quick release ([V2510801])	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO MS (kit V3990101 sold separately)	
Freewheel body: convertible SHIMANO MS (kit V3990101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB aluminium (kit V3780101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB aluminium (kit V3780101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9Â°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	

Specifications

RIMS

- **Material :** 100% carbon fiber with UDÂ² external layer
- **Material :** 100% carbon fiber with UDÂ² external layer
- **Height :** 25 mm
- **Height :** 25 mm
- **Internal width :** 30 mm
- **Internal width :** 30 mm
- **Drilling :** traditional (front/rear 28 holes)
- **Drilling :** traditional (front/rear 28 holes)

Disc brake specific profile
Disc brake specific profile
E-Bike specific rim profile
E-Bike specific rim profile

- **ETRTO size 29" :** 622x30TSS
- **ETRTO size 29" :** 622x30TSS
- **Tire :** clincher
- **Tire :** clincher

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** j-bent, round, 2.0 straight gauge
- **Shape :** j-bent, round, 2.0 straight gauge

Instant Drive 360 freewheel technology
12mm front hub cap ([V2680501])

WHEEL HUB

- **Body :** aluminum
- **Body :** aluminum
- **Body design :** INFINITY
- **Body design :** INFINITY
- **Disc standard :** 6 Bolts only
- **Disc standard :** 6 Bolts only
- **Axle material :** aluminum
- **Axle material :** aluminum
- **Rear body :** aluminum
- **Rear body :** aluminum
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Freewheel :** FTS-L steel
- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

Download date: 2024-07-16 / Update date: 2024-07-15