MAVIC Crossride Light WTS 27.5

ASTM CATEGORY 3 : offroad with jumps less than 61cm
Recommended weight limit : 120kg

REFERENCES WHEELS

F71541	XrdLight27.5Ft Boost WTS	F36901	Xride Light27.5Ft WTS





RIMS

Ã VALVE HOLE (MM): 8,5 WITH POP OFF REDUCER :

1	V2314515	"KIT FRONT/REAR RIM CROSSRIDE LIGHT 27,5"""

SPOKES

2	V2381801	KIT 12 FT/NDS XRIDE LIGHT 27,5'' SPK 277mm

HUB SHELLS

3	N/A	HUB BODY
4	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
5	V2370101	KIT FRONT AXLE 15MM CROSSONE/-RIDE/-ROC - while stock last
5	V2371101	KIT FRONT QRM AXLE 100mm/BOOST 110mm
6	V2370301	KIT FRONT AUTO ADJUSTING PLAY 15mm AXLE

Download date: 2024-07-16 / Update date: 2022-03-01

MAVIC Crossride Light WTS 27.5

DELIVERED WITH

Rim tape	
Rear 12x142mm adapters	
User guide	
Rear 12x142mm adapters for ITS4 and TS2 (308 593 01 for ITS4, 329 650 01 for TS2) 1	
Rim tape	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to XD with optional driver body	
Front axle: convertible from 15mm thru axle to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- **Joint :** sleeved
- **Drilling :** traditional

Disc brake specific profile

- **Valve hole diameter :** 8,5 mm with pop off reducer
- **Tyre :** tubetype
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C
- **ETRTO size 27.5" :** 584x21C
- **ETRTO size 29" :** 622x21C
- **Joint :** sleeved
- **Drilling :** traditional

Disc brake specific profile

- **Valve hole diameter :** 8,5 mm with pop off reducer
- **Tyre :** tubetype
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C
- **ETRTO size 27.5" :** 584x21C
- **ETRTO size 29" :** 622x21C

SPOKES

- **Material :** steel
- **Shape :** straight pull, bladed, double butted
- **Nipples :** brass, ABS
- **Count :** 24 front and rear
- **Material :** steel
- **Lacing :** front and rear crossed 2
- **Shape :** straight pull, bladed, double butted
- **Nipples :** steel, ABS
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2

WHEEL HUB

- **Freewheel :** TS-2 alloy
- **Front and rear bodies :** aluminum
- **Freewheel :** TS-2 alloy

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)

WHEEL WEIGHTS

Wheel weight
Weight Front 26": 850
Weight Front 27.5": 880
Weight Front 29": 930

Download date: 2024-07-16 / Update date: 2022-03-01