MAVIC E-DEEMAX 27.5

ASTM CATEGORY 5 : GRAVITY RIDING FOCUSED ON THE DESCENT
Minimum tyre size: width 52mm - pressure max. 2.95Bar/43PSI
Non-Boost : 12 to 9mm rear adapter for quick release ([V2510801])
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 180kg, E-bike included

REFERENCES WHEELS





Specifications	Maxi target
Frontal run out	0,5mm
Lateral run out	0,5mm
Centrering	1,0mm (2x0,5)
Tension daN Disc side	83 > 126

RIMS

 :

1	V00096431	Kit Front/Rear rim eDeemax 24 27,5''
	V3750101	35mm UST Green Tape for 30mm wide rims

SPOKES

2	V00096931	Kit 14 steel spokes 283mm eDeemax 24 27,5''

HUB SHELLS

3	N/A	HUB BODY
4	M40179	FRONT BEARING 25x37x7 20mm AXLE
5	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL
7	N/A	HUB BODY
8	V2373801	KIT 20x110mm AXLE QRM AUTO MTB > 2019

ADAPTERS

6	V2372501	15mm MTB Axle Cap QRM Auto From 2019

Download date: 2024-07-16 / Update date: 2024-07-15

MAVIC E-DEEMAX 27.5

DELIVERED WITH

User guide	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	
Pre-installed tubeless rim tape	
UST valve and accessories (129 838 01)	
2 replacement spokes with each wheel	
12 to 9mm rear adapter for quick release ([V2510801])	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB aluminium (kit V3780101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB aluminium (kit V3780101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Boost 20 to 15mm front adapter ([12982801]	
Front axle: for fixing nuts only (included), M9x1 thread	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9Â°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Height :** 22 mm
- **Height :** 22 mm
- **Joint :** SUP welding technology
- **Joint :** SUP welding technology
- **Internal width :** 30 mm
- **Internal width :** 30 mm
- **Drilling :** traditional (front/rear 28 holes)
- **Drilling :** traditional (front/rear 28 holes)

Disc brake specific profile
Disc brake specific profile
Asymmetrical rim design
Asymmetrical rim design

- **ETRTO size 27.5" :** 584x30TC
- **ETRTO size 27.5" :** 584x30TC
- **Tire :** clincher
- **Tire :** clincher

SPOKES

- **Material :** steel
- **Material :** steel
- **Lacing :** front and rear crossed 2, contactless
- **Lacing :** front and rear crossed 2, contactless

Instant Drive 360 freewheel technology
12mm front hub cap ([V2680501])

WHEEL HUB

- **Body :** aluminum
- **Body :** aluminum
- **Body design :** INFINITY
- **Body design :** INFINITY
- **Disc standard :** 6 Bolts or Center LockÂ®
- **Disc standard :** 6 Bolts or Center LockÂ®
- **Axle material :** aluminum
- **Axle material :** aluminum
- **Rear body :** aluminum
- **Rear body :** aluminum
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Rear :** Quick Release, 12x142 and 12x135 compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible
- **Freewheel :** FTS-L steel
- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

1016

Download date: 2024-07-16 / Update date: 2024-07-15