MAVIC Crossmax SL 27.5

2015
FRONT

REFERENCES WHEELS

F01501	Crossmax SL 27.5Ft





RIMS

VALVE HOLE Ã (MM): 6.5 :

1	V2310210	KIT FRONT RIM CROSSMAX SL/SL PRO BLACK 27,5''

SPOKES

2	36675001	"KIT 10 NDS XMAX SLR/ENDURO 27,5"" ALU SPK 281,5mm"

HUB SHELLS

3	N/A	HUB BODY
4	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
5	99688201	9/15 6B FRT AXLE CROSSMAX/KSY PRO CARBON SL C
6	10846501	FRONT FORK SUPPORT FOR 15mm AXLE

Download date: 2024-07-16 / Update date: 2022-03-01

MAVIC Crossmax SL 27.5

DELIVERED WITH

BX601 quick releases	
UST valve and accessories	
Front 15 mm adapters	
Rear QR adapters	
Rear 12x142mm adapters	
Specific disc bolts	
Computer magnet (front wheel)	
Multifonction adjustment wrench	
User guide	

Specifications

RIMS

- **Material :** Maxtal
- **Joint :** SUP
- **Drilling :** Fore

Disc brake specific profile

- **Weight reduction :** ISM4D
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 19 mm
- **ETRTO size 26" :** 559x19C
- **ETRTO size 650b/27.5" :** 584x19C
- **ETRTO size 29" :** 622x19C
- **Recommended tyre sizes :** 1.5 to 2.3

SPOKES

- **Material :** Zicral
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** 20 front and rear
- **Lacing :** front crossed 2, rear Isopulse

WHEEL HUB

- **Front body :** carbon with aluminum flanges
- **Rear body :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

Shimano 11 speeds compatible
XD Compatible (XX1-X01) with optionnal kit

WHEEL WEIGHTS

Wheel weight 665

Download date: 2024-07-16 / Update date: 2022-03-01