MAVIC XA Pro

ASTM CATEGORY 3 : CROSS COUNTRY AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 120kg, bike included
Recommended tyre sizes: 46mm to 64mm (1.8" to 2.5")

REFERENCES WHEELS

F80311	Xa Pro 27,5 Ft Bst	P86611	XA Pro 27,5 Pr XD
F80511	Xa Pro 27,5 Ft Lefty 60	P86621	XA Pro 27,5 Pr Bst XD
P86191	XA Pro 27,5 Pr	F80301	Xa Pro 27,5 Ft
P86351	XA Pro 27,5 Pr Bst		





RIMS

 :

1	V2318410	KIT FRONT RIM XA PRO 27,5''

SPOKES

2	V2384701	KIT 12 FT/NDS CROSSMAX PRO 27,5'' SPK 275mm
2	V2385501	KIT 1 FT/RR XA PRO 27,5'' BUTT ALU SPOK 275mm - while stock

HUB SHELLS

3	N/A	HUB BODY
4	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
5	V2252301	KIT MY16 FRONT AXLE ROAD DISC 9/12/15 INT
7	N/A	HUB BODY
8	V2370701	KIT FRONT QRM+ AXLE BOOST INTL 110mm
9	N/A	HUB BODY
10	M40771	BEARING KIT FOR LEFTY 50 & 60 HUB
11	36709301	ASSEMBLY KIT FOR LEFTY SUPERMAX WHEELS

OPTIONS

	V2650201	ADAPTER Front Torque Cap 15x31 MTB QRM +

ADAPTERS

6	B4104401	ADAPTER Ft 15mm QRM+
	B4104301	ADAPTER Ft 9mm QR QRM+

Download date: 2024-07-16 / Update date: 2022-05-31

MAVIC **XA Pro**

2018
FRONT

DELIVERED WITH

UST valve and accessories (129 838 01)	
Multifonction adjustment wrench (325 423 01)	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Front axle: convertible from 15mm thru axle to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- **Material :** Maxtal
- **Joint :** SUP
- **Drilling :** Fore
- **Weight reduction :** ISM 4D
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 25 mm
- **ETRTO size 27.5" :** 584x25TSS
- **ETRTO size 29" :** 622x25TSS

Hookless profile

SPOKES

- **Material :** Zicral
- **Shape :** straight pull, bladed, front double butted
- **Nipples :** Fore integrated aluminum
- **Count :** 24 front and rear
- **Lacing :** front crossed 2, rear Isopulse
- **Lacing :** front and rear crossed 2

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings (QRM+)

- **Freewheel :** ITS-4 alloy

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)

Lefty Supermax

WHEEL WEIGHTS

Weight Front 27.5": 745
Weight Front 29": 785

Download date: 2024-07-16 / Update date: 2022-05-31