

ASTM CATEGORY 3 : CROSS COUNTRY AND TRAIL RIDING

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 150kg, bike included


Recommended tyre sizes: 65mm to 81mm (2.5" to 3.2")

REFERENCES WHEELS

P88801 E-XA 35 27,5 Pr Bst

F82591 E-XA 35 27,5 Ft Boost

P88811 E-XA 35 27,5 Pr Bst XD



RIMS



&NBSP;:

1	V3763715	KIT FRT/REAR RIM E-XA 27,5"
	V3710101	40mm UST Tape For 35mm Wide Rims

SPOKES

2	V3821301	KIT 14 FRT/ND5 E-CROSSMAX/E-XA 27,5" FLAT SPOKE 282mm + nip
---	----------	---

HUB SHELLS

3	N/A	HUB BODY
4	M40179	FRONT BEARING 25x37x7 20mm AXLE
5	V2373701	KIT 20x110mm BOOST AXLE QRM AUTO MTB > 2019

OPTIONS

V2650401	TORQUECAP20*31 FT QRM AUTO MTB
----------	--------------------------------

ADAPTERS

6	V2680401	20x110 BOOST Front Adapter MTB wheels
	12982801	ADAPTER Ft 20 to 15mm



E-XA35

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Specific disc bolts (308 719 01)	
Specific disc bolts (308 719 01)	
Specific disc bolts (308 719 01)	
Tubeless rim tape	
Tubeless rim tape	
Tubeless rim tape	
User guide	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Freewheel: Shimano/Sram or XD	
Freewheel: Shimano Micro Spline	
Freewheel: Shimano Micro Spline	

Specifications

RIMS

- Material : S6000 Aluminum
- Material : S6000 Aluminum
- Material : S6000 Aluminum
- Joint : sleeved
- Joint : sleeved
- Joint : sleeved
- Drilling : traditional
- Drilling : traditional
- Drilling : traditional
- E-Bike specific rim profile
- E-Bike specific rim profile
- E-Bike specific rim profile
- Valve hole diameter : 6.5 mm
- Valve hole diameter : 6.5 mm
- Valve hole diameter : 6.5 mm
- Tyre : UST Tubeless and tubetype
- Tyre : UST Tubeless and tubetype
- Tyre : UST Tubeless and tubetype
- Internal width : 35 mm
- Internal width : 35 mm
- Internal width : 35 mm
- Internal width : 35 mm
- ETRTO size 27.5" : 584x35TSS
- ETRTO size 27.5" : 584x35TSS
- ETRTO size 27.5" : 584x35TSS

WHEEL HUB

- Front and rear bodies : aluminum
 - Front and rear bodies : aluminum
 - Front and rear bodies : aluminum
 - Axle material : aluminum
 - Axle material : aluminum
 - Axle material : aluminum
 - Auto adjust sealed cartridge bearings (QRM Auto), front and rear
 - Auto adjust sealed cartridge bearings (QRM Auto), front and rear
 - Freewheel : Instant Drive 360 steel
 - Freewheel : Instant Drive 360 steel
 - Instant Drive 360
 - QRM Auto
- VERSIONS
- Color : Black only
 - Color : Black only
 - Disc standard : 6 Bolts only
 - Disc standard : 6 Bolts only
 - Disc standard : 6 Bolts only
 - Hub width : Boost only (front 110, rear 148)
 - Hub width : Boost only (front 110, rear 148)
 - Hub width : Boost only (front 110, rear 148)
 - Hub width : Boost only (front 110, rear 148)
 - Freewheel : Shimano/Sram or XD

WHEEL WEIGHTS

939