MAVIC Crossmax XL Pro WTS 29

2016
FRONT

REFERENCES WHEELS

F35801	XmaxXLPro29Ft WTS	F69571	XmXLPro29FtSpxWTS



RIMS

Ã VALVE HOLE (MM): 6,5 :

1	V2310910	KIT FRONT RIM CROSSMAX XL 2015 29''

SPOKES

2	A7209901	KIT 12 FT/NDS CROSSMAX XL/DEEMAX PRO 19 29'' SPK 293mm

HUB SHELLS

3	N/A	HUB BODY
4	M40179	FRONT BEARING 25x37x7 20mm AXLE
5	30870501	FRONT AXLE 20mm CROSSMAX + DEEMAX ULTI 2012
7	N/A	HUB BODY
8	M40771	BEARING KIT FOR LEFTY 50 & 60 HUB
9	36709301	ASSEMBLY KIT FOR LEFTY SUPERMAX WHEELS

ADAPTERS

6	12982901	ADAPTER Ft 20x110mm

Download date: 2024-07-16 / Update date: 2022-03-01

MAVIC Crossmax XL Pro WTS 29

DELIVERED WITH

BX601 rear quick release	
1 bottle of Mavic Sealant	
UST valve and accessories	
Front 15 mm adapters	
Rear QR adapters	
Rear 12x142mm adapters	
Multifonction adjustment wrench	
User guide	

Specifications

RIMS

- **Material :** Maxtal
- **Drilling :** Fore
- **Weight reduction :** ISM
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 23 mm
- **ETRTO size 26" :** 559x23C
- **ETRTO size 27.5" :** 584x23C
- **ETRTO size 29" :** 622x23C
- **ETRTO recommended tyre sizes :** 37mm to 76mm (1.5" to 3.0")

SPOKES

- **Material :** Zicral
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** 24 front and rear
- **Lacing :** front crossed 2, rear Isopulse

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

Shimano 11 speeds compatible
Sram XD Compatible (XX1-X01) with optionnal kit

WHEEL WEIGHTS

Wheel weight
Weight Front 26": 790
Weight Front 27.5": 815
Weight Front 29": 850

Download date: 2024-07-16 / Update date: 2022-03-01