MAVIC COSMIC SL 32 LTD

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included
Recommended tire sizes: 25 to 32 mm
Max. Pressure: see indication on wheel and tire. If they differ, use the lowest of the 2

REFERENCES WHEELS



RIMS

 :

1	V00063531	Kit Front/Rear rim Cosmic SL32 Ltd
	V2620101	UST RIM TAPE 25mm (for 21-24mm wide rim)

SPOKES

2	V4163401	Kit 12 Front/Rear Cosmic SL 32 Disc butted stainless spoke 2

HUB SHELLS

3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2373401	KIT ID360 135/142 DCL L1 AXLE WITH CLIP
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V00063631	Kit ID360 seal version 2 (larger)
8	V2251701	KIT ID360 2 RATCHETS + SPRING + GREASE
9	V2500501	KIT ID360 3 PADS NOISE REDUCING
10	V2251801	KIT 3 ID360 ROAD SPRINGS
11	V3430101	HG11 Freewheel Body ID360
11	V2580101	FREEHUB BODY XD Road ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing

ADAPTERS

13	V2510701	ID360V2RrAxleAdapt12x142/148
	V2510901	ID360 EVO RrAxleAdpt12x135/150
	V2510801	ID360 V2 RrAxleAdapt9x135

MAVIC COSMIC SL 32 LTD

DELIVERED WITH

Front QR adapters	
Rear QR adapters for Instant Drive 360 (B49 894 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo ED11, N3W and XD-R with optional driver bodies	
Front axle: 12x100 thru axle, easily convertible to quick release with included adapters. Not compatible with 15mm through axles.	
Rear axle: 12mm thru axle, convertible to Quick Release with included adapters	

Specifications

RIMS

- **Material :** 100% carbon fiber
- **Height :** 32mm
- **Drilling :** traditional

Disc brake specific profile

- **Tire :** UST Tubeless and tubetype
- **Internal width :** 21 mm
- **ETRTO size :** 622x21TC

UST tubeless technology

SPOKES

- **Material :** steel
- **Shape :** straight pull, flat, double butted
- **Nipples :** brass, ABS
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless

WHEEL HUB

Infinity hubs

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Instant Drive 360 freewheel technology

QRM Auto bearing preload technology

- **Front :** Quick release and 12x100 through axle compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible

Hub available for Center Lock brake rotors only

VERSIONS

- **Disc standard :** Center LockÂ® only
- **Freewheel :** Shimano/Sram

WHEEL WEIGHTS

807

Download date: 2024-07-16 / Update date: 2024-02-15