


## REFERENCES WHEELS

R37501 Aksium One Disc Rr CL

R19801 Aksium One Disc Rr INT



### RIMS



VALVE HOLE  $\bar{A}$  (MM): 6.5 :

1 V2290815 KIT FRT/REAR RIM AKSIUM ONE DISC/AKSIUM DISC

### SPOKES

2 36690301 "KIT 12 FT/NDS XONE/XMAX - XA 29"/AKSIUM DISC 9 + 12 FT/AKS  
3 36690401 KIT 12 DS XONE/XRIDE FTSX/AKSIUM DISC 9 SPK 294mm

### HUB SHELLS

4 N/A HUB BODY  
6 M40660 REAR HUB 608+6001 BEARINGS  
7 30871101 FTS-L ROAD FREEWHEEL BODY HG11 8/9 compatible  
8 30871201 FTS-L ROAD FREEWHEEL BODY ED11 8/9 compatible  
9 M40067 INTERNAL FREEWHEEL SPACER FTSL/FTSX  
10 99500001 FTSL/FTSX FREEHUB BODY SEAL  
11 32348401 EXPANSIBLE BEARINGS SUPPORT  
12 32348001 MTB DISC REAR AXLE QRM MTB DISC

# MAVIC Aksium One Disc

## DELIVERED WITH

BR101 quick releases	
Rim tape	
Front QR adapters	
User guide	

## Specifications

### RIMS

- **Material** : S6000 Aluminum
- **Height** : 22mm
- **Joint** : pinned
- **Drilling** : traditional with H2 reinforcement
- Disc brake specific profile
- **Valve hole diameter** : 6.5 mm
- **Tyre** : clincher
- **ETRTO size** : 622x17C
- **Recommended tyre sizes** : 25 to 52 mm

### SPOKES

- **Material** : steel
- **Shape** : straight pull, round
- **Nipples** : brass, ABS
- **Count** : 24 front and rear
- **Lacing** : front and rear crossed 2

### WHEEL HUB

- **Front and rear bodies** : aluminum
- **Body** : aluminum
- **Axle material** : front aluminum, rear steel
- Sealed cartridge bearings
- **Freewheel** : FTS-L steel

### WHEEL WEIGHTS

Wheel weight 1075