

ASTM CATEGORY 1 : road only

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included

Recommended tyre sizes: 25 to 52 mm


Max. Pressure: 25mm 7.7 bars - 110 PSI

参照ホイール

R71801 CosProCarbSLDiscINTRr

R72201

CosProCarbSLDiscCLRr



RIMS



25.7mm x 17mm x 40.1mm (21mm x 6.5mm)

1	V2733313	KIT REAR RIM COSMIC PRO CARBON SL UST DISC
1	V2401313	KIT RR RIM COSMIC PRO CARBON SL Disc - while stock last
	V2620101	UST RIM TAPE 25mm (for 21-24mm wide rim)
	V2690101	KIT CARBON RIM TAPE 21x622mm (SPECIAL RIM TAPE)

SPOKES

2	V2271101	KIT 12 DS COS PRO CARB SL/SL UST 1 UST D BTD AERO SPK
2	V3662801	KIT 12 DS COSMIC PRO CARB SL T/UST/UST Disc/C/C Disc BUTTED
3	V3663001	KIT 12 FRT/NDS COSMIC PRO CARB SL UST/UST Disc C/C Disc/T Di
3	V2271201	KIT 12 NDS COS PRO CARB SL/FT SL D/FT & NDS UST & UST D SPK

HUB SHELLS

4	N/A	HUB BODY
4	N/A	HUB BODY
5	V2560201	KIT ID360 BEARINGS 15/28/7 + 17/28/7
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V2251601	ID360 SEAL + GREASE
8	V2500501	Kit 3 ID360 pad for noise reduction
9	V2251701	ID360 2 RATCHETS + SPRING + GREASE
10	V2251801	KIT 3 ID360 ROAD SPRINGS
11	V3430101	HG11 Freewheel Body ID360
12	V2252201	KIT 2 REAR HUB RETENTION RINGS 48mm

13	V2251501	3 ID360 WAVE WASHERS
14	V2251301	ID360 AXLE DISC 6T
15	V2251001	KIT ID360 HUB THREADED CAP UB+DISC 6 BOLTS (large) - while s
17	N/A	HUB BODY
17	N/A	HUB BODY
18	V2251401	ID360 AXLE DISC CL
20	V2251101	KIT ID360 HUB THREADED CAP DISC CENTER LOCK

ADAPTERS

16	B4989601	Rear Axle Adapters 12/142 INT
19	B4989901	Rear Axle Adapters 12/142 CL

付属品

Rim tape	
Front 12 mm adapters	
Specific disc bolts	
Multifonction adjustment wrench	
User guide	
Front 12 mm adapters (B4104201) 1	
Rear 12x142mm adapters for Instant Drive 360 (B49 896 01 for ID360 6T, B49 899 01 for ID360 CL) 1	
Specific disc bolts	
Rim tape	
Multifonction adjustment wrench	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or Campagnolo, convertible to XD-R with optional driver body	
Front axle: convertible from 12mm thru axle to quick release or 15mm thru axle with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapaters	

Specifications

リム

- Material：3K carbon fibers
- Height：40 mm
- Material：3K carbon fibers
- Drilling：traditional
- Disc brake specific profile
- Valve hole diameter：6.5 mm
- Tyre：clincher
- Internal width：17 mm
- ETRTO size：622x17C
- Recommended tyre sizes：25 to 52 mm
- Height：40 mm
- Drilling：traditional
- Disc brake specific profile
- Valve hole diameter：6.5 mm
- Tyre：clincher
- Internal width：17 mm
- ETRTO size：622x17C

スポーク

- Material：steel
- Shape：straight pull, bladed, double butted
- Nipples：aluminum, ABS
- Count：24 front and rear
- Material：steel
- Lacing：front crossed 2, rear Isopulse
- Shape：straight pull, bladed, double butted
- Nipples：aluminum, ABS
- Count：24 front and rear
- Lacing：front crossed 2, rear Isopulse

ホイールハブ

- Front and rear bodies：aluminum
- Axle material：aluminum
- Sealed cartridge bearings
- Freewheel：Instant Drive 360
- Front and rear bodies：aluminum
- Front：Quick release, 12 thru and 15 thru compatible
- Axle material：aluminum
- Rear：12x142 (convertible to quick release with optional adapters)
- Sealed cartridge bearings
- Freewheel：Instant Drive 360
- Front：Quick release, 12 thru and 15 thru compatible
- Rear：12x142 (convertible to quick release with optional adapters)

VERSIONS

- Color：Black only
- Disc standard：6 Bolts or Center Lock(R)

ホイールの重み

ホイール重量 (クイックリリース
スおよびクリンチャー/チュー
ブラーを除く) (g)：820