MAVIC CXR Ultimate 60 T

ASTM CATEGORY 1 : road only
Recommended weight limit : 120kg
Recommended tyre size: 23 mm

REFERENCES WHEELS

F33201	CXRUlti60T16Ft





RIMS

VALVE HOLE Ã (MM): 6,5 :

1	V2403510	KIT FRONT RIM CXR60T 2016
1	32979310	KIT FRONT RIM CXR 60 TUBULAR - while stock last

SPOKES

2	32979601	KIT 10 AERO FT/NDS CXR 60 T BLK SPOKE 255mm

HUB SHELLS

3	N/A	HUB BODY
4	M40078	FRONT HUB BEARINGS 6901 x 2
5	30870001	FRONT AXLE ROAD RIM BRAKING QRM +
6	32985701	HUB CAP & ADJUSTING NUT CXR 80

ADAPTERS

7	35117301	FT/RR FORK REST R-SYS/CC ULTIMATE > 2013/KSY PRO CARB T

Download date: 2024-07-16 / Update date: 2022-03-01

MAVIC CXR Ultimate 60 T

DELIVERED WITH

BR601 quick releases	
BR601 quick releases	
CXR specific carbon brake pads	
Valve extender	
CXR specific carbon brake pads	
Multifonction adjustment wrench	
User guide	
Valve extender	
Multifonction adjustment wrench	
User guide	

Specifications

RIMS

- **Material :** 100% woven 3K carbon fiber
- **Height :** 60 mm, Width 27 mm with CX01 groves
- **Material :** 100% woven 3K carbon fiber
- **Drilling :** traditional
- **Brake track :** carbon
- **Valve hole diameter :** 6.5 mm
- **Tyre :** tubular
- **ETRTO size :** 28" tubular
- **Recommended tyre size :** 23 mm
- **Height :** 60 mm, Width 27 mm with CX01 groves
- **Drilling :** traditional
- **Brake track :** carbon
- **Valve hole diameter :** 6.5 mm
- **Tyre :** tubular
- **ETRTO size :** 28" tubular

SPOKES

- **Material :** steel
- **Shape :** straight pull, bladed, double butted
- **Nipples :** aluminum, ABS
- **Count :** front 16, rear 20
- **Material :** steel
- **Lacing :** radial front and rear non-drive side, crossed 2 rear drive side
- **Shape :** straight pull, bladed, double butted
- **Nipples :** aluminum, ABS
- **Count :** front 16, rear 20
- **Lacing :** radial front and rear non-drive side, crossed 2 rear drive side

WHEEL HUB

- **Front and rear bodies :** carbon center tube and aluminum flanges
- **Front and rear bodies :** carbon center tube and aluminum flanges
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** FTS-L steel
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

Wheel weight 710

Download date: 2024-07-16 / Update date: 2022-03-01