


ASTM CATEGORY 1 : road only  
Recommended weight limit : 120kg  
Recommended tyre sizes: 25 to 52 mm  
Max. Pressure: 25mm 7.7 bars - 110 PSI

### REFERENCES WHEELS

F43101 CosProCarbSLDiscINTFt

F43501 CosProCarbSLDiscCLFt



### RIMS



VALVE HOLE  $\bar{A}$  (MM): 6,5 :

|   |          |                                                          |
|---|----------|----------------------------------------------------------|
| 1 | V2401210 | KIT FRT RIM COSMIC PRO CARBON SL Disc - while stock last |
| 1 | V2733210 | KIT FRONT RIM COSMIC PRO CARBON SL UST DISC              |
|   | V2690101 | KIT CARBON RIM TAPE 21x622mm - FOR CARBON RIM            |
|   | V2620101 | UST RIM TAPE 25mm (for 21-24mm wide rim)                 |

### SPOKES

|   |          |                                                              |
|---|----------|--------------------------------------------------------------|
| 2 | V3663001 | KIT 12 FRT/NDS COSMIC PRO CARB SL UST/UST Disc C/C Disc/T Di |
| 2 | V2271201 | KIT 12 NDS COS PRO CARB SL/FT SL D/FT & NDS UST & UST D SPK  |

### HUB SHELLS

|    |          |                                                      |
|----|----------|------------------------------------------------------|
| 3  | N/A      | HUB BODY                                             |
| 4  | 99688601 | BEARING KIT 9/15 DCL HUB 20x32x7 6804 + 25x37x7 6805 |
| 5  | V2252401 | KIT MY16 FRONT AXLE ROAD DISC 9/12/15 CL             |
| 10 | 99688501 | BEARING KIT 9/12/15 D6T HUB 20x32x7 6804             |
| 11 | V2252301 | KIT MY16 FRONT AXLE ROAD DISC 9/12/15 INT            |

### ADAPTERS

|   |          |                        |
|---|----------|------------------------|
| 6 | B4104301 | ADAPTER Ft 9mm QR QRM+ |
| 7 | B4104201 | ADAPTER Ft 12mm QRM+   |
| 8 | B4104401 | ADAPTER Ft 15mm QRM+   |

# MAVIC Cosmic Pro Carbon SL C Disc

## DELIVERED WITH

|                                                                                                         |                                                                                   |
|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Rim tape                                                                                                |                                                                                   |
| Front 12 mm adapters                                                                                    |                                                                                   |
| Specific disc bolts                                                                                     |                                                                                   |
| Multifunction adjustment wrench                                                                         |                                                                                   |
| User guide                                                                                              |                                                                                   |
| Front 12 mm adapters<br>(B4104201)<br>1                                                                 |  |
| Rear 12x142mm adapters for Instant Drive 360<br>(B49 896 01 for ID360 6T, B49 899 01 for ID360 CL)<br>1 |  |
| Specific disc bolts                                                                                     |                                                                                   |
| Rim tape                                                                                                |                                                                                   |
| Multifunction adjustment wrench                                                                         |                                                                                   |
| User guide                                                                                              |                                                                                   |

## COMPATIBILITY

|                                                                                                       |  |
|-------------------------------------------------------------------------------------------------------|--|
| Freewheel: Shimano/Sram or Campagnolo, convertible to XD-R with optional driver body                  |  |
| Front axle: convertible from 12mm thru axle to quick release or 15mm thru axle with optional adapters |  |
| Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters                        |  |

## Specifications

### RIMS

- **Material** : 3K carbon fibers
- **Height** : 40 mm
- **Drilling** : traditional
- **Material** : 3K carbon fibers
- Disc brake specific profile
- **Valve hole diameter** : 6.5 mm
- **Tyre** : clincher
- **Internal width** : 17 mm
- **ETRTO size** : 622x17C
- **Recommended tyre sizes** : 25 to 52 mm
- **Height** : 40 mm
- **Drilling** : traditional
- Disc brake specific profile
- **Valve hole diameter** : 6.5 mm
- **Tyre** : clincher
- **Internal width** : 17 mm
- **ETRTO size** : 622x17C

### SPOKES

- **Material** : steel
- **Shape** : straight pull, bladed, double butted
- **Nipples** : aluminum, ABS
- **Count** : 24 front and rear
- **Lacing** : front crossed 2, rear Isopulse
- **Material** : steel
- **Shape** : straight pull, bladed, double butted
- **Nipples** : aluminum, ABS
- **Count** : 24 front and rear
- **Lacing** : front crossed 2, rear Isopulse

### WHEEL HUB

- **Front and rear bodies** : aluminum
- **Axle material** : aluminum
- Sealed cartridge bearings
- **Freewheel** : Instant Drive 360
- **Front and rear bodies** : aluminum
- **Front** : Quick release, 12 thru and 15 thru compatible
- **Axle material** : aluminum
- **Rear** : 12x142 (convertible to quick release with optional adapters)
- Sealed cartridge bearings
- **Freewheel** : Instant Drive 360
- **Front** : Quick release, 12 thru and 15 thru compatible
- **Rear** : 12x142 (convertible to quick release with optional adapters)

### VERSIONS

- **Color** : Black only
- **Disc standard** : 6 Bolts or Center Lock(R)

### WHEEL WEIGHTS

Wheel weight 750