MAVIC DEEMAX DH 29

ASTM CATEGORY 5 : GRAVITY RIDING FOCUSED ON THE DESCENT
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Minimum tyre size: width 52mm - pressure max. 2.95Bar/43PSI
Non-Boost : 12 to 9mm rear adapter for quick release ([V2510801])

REFERENCES WHEELS



Specifications	Maxi target
Frontal run out	0,5mm
Lateral run out	0,5mm
Centrering	1,0mm (2x0,5)
Tension daN Disc side	99 > 119

RIMS

 :

1	V00094431	"Kit front/rear Deemax DH 23 29"""
	V3750101	35mm UST Green Tape for 30mm wide rims

SPOKES

2	V2387901	KIT 14 J BENT STEEL SPOKES 299mm DEEMAX DH 29'' + black stee

HUB SHELLS

3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2372201	KIT ID360 148 D6T AXLE WITH CLIP
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V2251601	KIT ID360 SEAL + GREASE
8	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
9	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
10	V2372901	KIT 3 ID360 MTB SPRINGS
11	V3740101	XD MTB Freewheel Body ID360
11	V3990101	MicroSpline MTB Freewheel Body ID360
11	V3780101	HG9 Alloy MTB Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
13	N/A	HUB BODY
14	V2374801	Kit ID360 150/157 D6T AXLE WITH CIRCLIP

OPTIONS

8	V2372801	KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD

ADAPTERS

15	V2510701	ID360V2RrAxleAdapt12x142/148

MAVIC DEEMAX DH 29

DELIVERED WITH

User guide	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	
Pre-installed tubeless rim tape	
UST valve and accessories (129 838 01)	
2 replacement spokes with each wheel	
12 to 9mm rear adapter for quick release ([V2510801])	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Boost & Non-Boost : 15mm front hub cap ([V2372501])	
15mm axle ([V2373501])	
ID360 Shimano / Sram freewheel body ([V3430101] - Delivered on the wheel)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9Â°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	
ID360 Shimano / Sram freewheel body ([V3430101] - Delivered on the wheel)	

Specifications

RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Height :** 22 mm
- **Height :** 22 mm
- **Joint :** SUP welding technology
- **Joint :** SUP welding technology
- **Internal width :** 30 mm
- **Internal width :** 30 mm
- **Drilling :** traditional (front/rear 28 holes)
- **Drilling :** traditional (front/rear 28 holes)

Disc brake specific profile
Disc brake specific profile
Asymmetrical rim design
Asymmetrical rim design

- **ETRTO size 29" :** 622x30TC
- **ETRTO size 29" :** 622x30TC
- **Tire :** clincher
- **Tire :** clincher

SPOKES

- **Material :** steel
- **Material :** steel
- **Count :** 32 front and rear
- **Count :** 32 front and rear

Instant Drive 360 freewheel technology
12mm front hub cap ([V2680501])

WHEEL HUB

- **Body :** aluminum
- **Body :** aluminum
- **Disc standard :** 6 Bolts only
- **Disc standard :** 6 Bolts only
- **Axle material :** aluminum
- **Axle material :** aluminum

Infinity hubs
Infinity hubs

- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Freewheel :** Shimano HG MTB / Shimano MS / Sram XD MTB
- **Freewheel :** Shimano HG MTB / Shimano MS / Sram XD MTB
- **Freewheel :** FTS-L steel
- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

1080

Download date: 2024-07-16 / Update date: 2024-07-15