MAVIC DEEMAX ENDURO SL 29

ASTM CATEGORY 5 : GRAVITY RIDING FOCUSED ON THE DESCENT
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Minimum tyre size: width 52mm - pressure max. 2.95Bar/43PSI
Non-Boost : 12 to 9mm rear adapter for quick release ([V2510801])

REFERENCES WHEELS

Specifications	Maxi target
Frontal run out	0,5mm
Lateral run out	0,5mm
Centrering	1,0mm (2x0,5)
Tension daN FWB side	112 > 136



RIMS

 :

1	V00094631	Kit Front/Rear rim Deemax Enduro SL 29''

SPOKES

2	V00095231	Kit 14 steel spokes 305mm Deemax Enduro SL 29''

HUB SHELLS

3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2372201	KIT ID360 148 D6T AXLE WITH CLIP
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V2251601	KIT ID360 SEAL + GREASE
8	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
9	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
10	V2372901	KIT 3 ID360 MTB SPRINGS
11	V3990101	MicroSpline MTB Freewheel Body ID360
11	V3780101	HG9 Alloy MTB Freewheel Body ID360
11	V3740101	XD MTB Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing

OPTIONS

8	V2372801	KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD

ADAPTERS

15	V2510701	ID360V2RrAxleAdapt12x142/148

Download date: 2024-07-16 / Update date: 2024-07-15

MAVIC DEEMAX ENDURO SL 29

DELIVERED WITH

User guide	
UST valve and accessories (129 838 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
UST valve and accessories (129 838 01)	
2 replacement spokes with each wheel	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
15mm axle ([V2373501])	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
ID360 Shimano / Sram freewheel body ([V3430101] - Delivered on the wheel)	

Specifications

RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Height :** 22 mm
- **Height :** 22 mm
- **Joint :** SUP welding technology
- **Joint :** SUP welding technology
- **Internal width :** 30 mm
- **Internal width :** 30 mm
- **Drilling :** Fore tapeless tubeless technology (front/rear 28 holes)
- **Drilling :** Fore tapeless tubeless technology (front/rear 28 holes)

Disc brake specific profile
Disc brake specific profile
Asymmetrical rim design
Asymmetrical rim design

- **ETRTO size 29" :** 622x30TC
- **ETRTO size 29" :** 622x30TC
- **Tire :** UST Tubeless and tubetype
- **Tire :** UST Tubeless and tubetype

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** j-bent, round, 2.0 straight gauge
- **Shape :** j-bent, round, 2.0 straight gauge
- **Front axle :** convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)
- **Boost :** Torque Caps ([V2650401])

12mm front hub cap ([V2680501])

WHEEL HUB

- **Body :** aluminum
- **Body :** aluminum
- **Body design :** INFINITY
- **Body design :** INFINITY
- **Disc standard :** 6 Bolts only
- **Disc standard :** 6 Bolts only
- **Axle material :** aluminum
- **Axle material :** aluminum
- **Axle size :** front 15x110 / rear 12x148

Hub available with 6-bolt or Center LockÂ® brake rotors

- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Freewheel :** Shimano HG MTB / Shimano MS / Sram XD MTB
- **Freewheel :** Shimano HG MTB / Shimano MS / Sram XD MTB
- **Freewheel :** FTS-L steel
- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

1035

Download date: 2024-07-16 / Update date: 2024-07-15