MAVIC Crossmax XL Pro WTS 27.5

ASTM CATEGORY 4 : offroad with jumps less than 122cm
Recommended weight limit : 120kg

REFERENCES WHEELS

R78901	XmXLPro27.5RrXD WTS	R59701	XmaxXLPro27.5RrWTS



RIMS

Ã VALVE HOLE (MM): 6,5 :

1	V2311113	KIT REAR RIM CROSSMAX XL 2015 27,5''

SPOKES

2	36675101	"KIT 10 DS XMAX SLR/END/PRO/DEEMAX PRO 27,5"" SPK 251,5mm"
3	36674901	KIT 12 FT XMAX END/FT-NDS DEEMAX PRO 27,5'' ALU SPK 275mm

HUB SHELLS

4	N/A	HUB BODY
5	M40076	HUB BEARINGS 17x30x7 6903 x 2
6	35126001	ITS-4 FREEWHEEL BODY + SEAL 2013 (NO PAWLS)
7	99610701	ITS-4 FREEWHEEL SEAL
8	99610601	PAWLS KIT FOR ITS-4 (OR TS-2)
9	30870401	REAR QRM + AXLE KIT ITS4 135mm from 2012
11	30871801	ELASTIC RING 56mm diam. ITS-4 20 SPOKES

ADAPTERS

10	30872201	FRAME SUPPORT ITS-4 135mm REAR AXLE > 2012

Download date: 2024-07-16 / Update date: 2022-03-01

MAVIC Crossmax XL Pro WTS 27.5

DELIVERED WITH

BX601 rear quick release	
1 bottle of Mavic Sealant	
UST valve and accessories	
Front 15 mm adapters	
Rear QR adapters	
Rear 12x142mm adapters	
Multifonction adjustment wrench	
User guide	

Specifications

RIMS

- **Material :** Maxtal
- **Drilling :** Fore
- **Weight reduction :** ISM
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 23 mm
- **ETRTO size 26" :** 559x23C
- **ETRTO size 27.5" :** 584x23C
- **ETRTO size 29" :** 622x23C
- **ETRTO recommended tyre sizes :** 37mm to 76mm (1.5" to 3.0")

SPOKES

- **Material :** Zicral
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** 24 front and rear
- **Lacing :** front crossed 2, rear Isopulse

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

Shimano 11 speeds compatible
Sram XD Compatible (XX1-X01) with optionnal kit

WHEEL WEIGHTS

Wheel weight
Weight Rear 26": 870
Weight Rear 27.5": 895
Weight Rear 29": 930

Download date: 2024-07-16 / Update date: 2022-03-01