

# MAVIC COSMIC SL 45 DISC MAHLEX20

2023 FRONT

REFERENCES WHEELS

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm

Maximum tyre pressure: 4.4bar/64PSI with a 28mm tyre - 2.6bar/38PSI with a 64mm tyre

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included

Maximum tyre size: width 62mm - pressure max. 3.8Bar/55PSI



## MAVIC COSMIC SL 45 DISC MAHLEX20

2023 FRONT

## **DELIVERED WITH**

User guide	
Maria Language Language	
Mavic tyre sealant (rear wheel) (355 466 01)	
UST valve and accessories (129 838 01)	
,	
Pre-installed tubeless rim tape	
User guide	
Pre-installed tubeless rim tape	
UST valve and accessories	
(129 838 01)	
12 to 9mm rear adapter for quick release	
([V2510801])	

## **Specifications**

## RIMS

- Material: 100% carbon fiber - Material: 100% carbon fiber

- Height: 45 mm • Height: 45 mm

**SPOKES** 

• Drilling: traditional (front/rear 28 holes) - Drilling: traditional (front/rear 28 holes)

Disc brake specific profile Disc brake specific profile • ETRTO size: 622x19TC ■ ETRTO size: 622x19TC • Tire : clincher • Tire: clincher

• Lacing: front radial, rear crossed 2 • Lacing: front radial, rear crossed 2 Instant Drive 360 freewheel technology

## WHEEL HUB

- Body: aluminum Body: aluminumBody design: INFINITY - Body design : INFINITY • Disc standard: 6 Bolts only - Disc standard: 6 Bolts only WHEEL WEIGHTS

## **COMPATIBILITY**

Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	
FTS-L Shimano / Sram freewheel body ([30871101] - Delivered on the wheel)	