MAVIC E-Deemax Pro 27,5

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 150kg, bike included
Recommended tyre sizes: 50mm to 76mm (2.0" to 3.0")

REFERENCES WHEELS

F83621	E-Deemax Pro 27,5 19 Ft	F83631	E-Dmx Pro 27,5 19 Ft Boost





RIMS

 :

1	V3760210	KIT FRONT RIM DEEMAX PRO 19 27,5''

SPOKES

2	V2386101	KIT 1 FRT/1 NDS STAMPED SPOKES 275mm DEEMAX PRO - while stoc
2	V2384701	KIT 12 FT/NDS CROSSMAX PRO 27,5'' SPK 275mm

HUB SHELLS

3	N/A	HUB BODY
4	M40179	FRONT BEARING 25x37x7 20mm AXLE
5	30870501	FRONT AXLE 20mm CROSSMAX + DEEMAX ULTI 2012
7	N/A	HUB BODY
8	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
9	V2370701	KIT FRONT QRM+ AXLE BOOST INTL 110mm

OPTIONS

	V2650201	ADAPTER Front Torque Cap 15x31 MTB QRM +

ADAPTERS

6	12982901	ADAPTER Ft 20x110mm
10	B4104401	ADAPTER Ft 15mm QRM+
	B4104301	ADAPTER Ft 9mm QR QRM+
	12982801	ADAPTER Ft 20 to 15mm
	12982701	ADAPTER Ft 20 to 9mm QR incl.

Download date: 2024-07-16 / Update date: 2022-04-15

MAVIC E-Deemax Pro 27,5

DELIVERED WITH

Computer magnet (105 416 01)	
Computer magnet (105 416 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Specific disc bolts (308 719 01)	
Specific disc bolts (308 719 01)	
Multifonction adjustment wrench (325 423 01)	
Multifonction adjustment wrench (325 423 01)	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Freewheel: Shimano/Sram or XD	
Front axle: 20mm, convertible to 15mm thru axle with optional adapters	
Front axle: 20mm, convertible to 15mm thru axle with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Freewheel: Shimano Micro Spline	
Freewheel: Shimano Micro Spline	

Specifications

RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Joint :** SUP
- **Joint :** SUP
- **Drilling :** Fore
- **Drilling :** Fore
- **Weight reduction :** ISM 4D
- **Weight reduction :** ISM 4D
- **Valve hole diameter :** 6.5 mm
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 28 mm
- **Internal width :** 28 mm

Hookless profile
Hookless profile

- **ETRTO size 27.5" :** 584x28TSS
- **ETRTO size 27.5" :** 584x28TSS

SPOKES

- **Material :** Zicral
- **Material :** Zicral
- **Shape :** straight pull, flat front and rear drive side and flat, double butted rear non drive side
- **Shape :** straight pull, flat front and rear drive side and flat, double butted rear non drive side
- **Nipples :** Fore integrated aluminum
- **Nipples :** Fore integrated aluminum
- **Count :** 24 front and rear
- **Count :** 24 front and rear
- **Lacing :** front crossed 2, rear Isopulse
- **Lacing :** front crossed 2, rear Isopulse

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Front bearings :** adjustable sealed cartridge bearings (QRM+), Rear bearings auto adjust sealed cartridge bearings (QRM Auto)
- **Front bearings :** adjustable sealed cartridge bearings (QRM+), Rear bearings auto adjust sealed cartridge bearings (QRM Auto)
- **Freewheel :** Instant Drive 360 steel
- **Freewheel :** Instant Drive 360 steel

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only
- **Disc standard :** 6 Bolts only
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)
- **Freewheel :** Shimano/Sram or XD
- **Freewheel :** Shimano/Sram or XD

WHEEL WEIGHTS

845

Download date: 2024-07-16 / Update date: 2022-04-15