MAVIC E-CROSSMAX XLR 29

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Minimum tyre size: width 52mm - pressure max. 2.35Bar/34PSI
Non-Boost : 15 to 9mm front adapter for quick release ([99694101])

REFERENCES WHEELS



RIMS

 :

1	V00101631	KIT FT/RR RIM E XTRAIL SL CARB

SPOKES

2	V00101831	KIT 14 SPK 298 EXTRAIL SL CARB

HUB SHELLS

3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2372201	KIT ID360 148 D6T AXLE WITH CLIP
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V2251601	KIT ID360 SEAL + GREASE
8	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
9	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
10	V2372901	KIT 3 ID360 MTB SPRINGS
11	V3990101	MicroSpline MTB Freewheel Body ID360
11	V3740101	XD MTB Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
13	N/A	HUB BODY
14	V2375701	Kit ID360 148 DCL axle with circlip

OPTIONS

	V2372801	KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD

ADAPTERS

15	V2510701	ID360V2RrAxleAdapt12x142/148

Download date: 2024-07-16 / Update date: 2024-07-15

MAVIC E-CROSSMAX XLR 29

DELIVERED WITH

User guide	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	
Pre-installed tubeless rim tape	
UST valve and accessories (129 838 01)	
2 replacement spokes with each wheel	
12 to 9mm rear adapter for quick release ([V2510801])	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO MS (kit V3990101 sold separately)	
Freewheel body: convertible SHIMANO MS (kit V3990101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB aluminium (kit V3780101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB aluminium (kit V3780101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9Â°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	

Specifications

RIMS

- **Material :** 100% carbon fiber with UDÂ² external layer
- **Material :** 100% carbon fiber with UDÂ² external layer
- **Height :** 25 mm
- **Height :** 25 mm
- **Internal width :** 30 mm
- **Internal width :** 30 mm
- **Drilling :** traditional (front/rear 28 holes)
- **Drilling :** traditional (front/rear 28 holes)

Disc brake specific profile
Disc brake specific profile
E-Bike specific rim profile
E-Bike specific rim profile

- **ETRTO size 29" :** 622x30TSS
- **ETRTO size 29" :** 622x30TSS
- **Tire :** clincher
- **Tire :** clincher

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** j-bent, round, 2.0 straight gauge
- **Shape :** j-bent, round, 2.0 straight gauge

Instant Drive 360 freewheel technology
12mm front hub cap ([V2680501])

WHEEL HUB

- **Body :** aluminum
- **Body :** aluminum
- **Body design :** INFINITY
- **Body design :** INFINITY
- **Disc standard :** 6 Bolts only
- **Disc standard :** 6 Bolts only
- **Axle material :** aluminum
- **Axle material :** aluminum
- **Rear body :** aluminum
- **Rear body :** aluminum
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Freewheel :** FTS-L steel
- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

Download date: 2024-07-16 / Update date: 2024-07-15