MAVIC Crossmax SL

2015
FRONT

REFERENCES WHEELS

F01401	Crossmax SL 26Ft





RIMS

VALVE HOLE Ã (MM): 6.5 :

1	V2310110	KIT FRONT RIM CROSSMAX SL/SL PRO BLACK 26''

SPOKES

2	30864201	KIT 10 FT/NDS M7/7 CROSSMAX SLR 12 SPK 269mm

HUB SHELLS

3	N/A	HUB BODY
4	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
5	99688201	9/15 6B FRT AXLE CROSSMAX/KSY PRO CARBON SL C
6	10846501	FRONT FORK SUPPORT FOR 15mm AXLE

Download date: 2024-07-16 / Update date: 2022-03-01

MAVIC Crossmax SL

DELIVERED WITH

BX601 quick releases	
UST valve and accessories	
Front 15 mm adapters	
Rear QR adapters	
Rear 12x142mm adapters	
Specific disc bolts	
Computer magnet (front wheel)	
Multifonction adjustment wrench	
User guide	

Specifications

RIMS

- **Material :** Maxtal
- **Joint :** SUP
- **Drilling :** Fore

Disc brake specific profile

- **Weight reduction :** ISM4D
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 19 mm
- **ETRTO size 26" :** 559x19C
- **ETRTO size 650b/27.5" :** 584x19C
- **ETRTO size 29" :** 622x19C
- **Recommended tyre sizes :** 1.5 to 2.3

SPOKES

- **Material :** Zicral
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** 20 front and rear
- **Lacing :** front crossed 2, rear Isopulse

WHEEL HUB

- **Front body :** carbon with aluminum flanges
- **Rear body :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

Shimano 11 speeds compatible
XD Compatible (XX1-X01) with optionnal kit

WHEEL WEIGHTS

Wheel weight
Weight Front 26": 630
Weight Front 27.5": 665
Weight Front 29": 690

Download date: 2024-07-16 / Update date: 2022-03-01