MAVIC Crossride Tubeless Quest 29

ASTM CATEGORY 3 : offroad with jumps less than 61cm
Recommended weight limit : 120kg
ETRTO recommended tyre sizes: 35mm to 69mm (1.4" to 2.7")

REFERENCES WHEELS

R60701	XrideUST Quest29RrWTS	R99171	XrdUSTQuest29 Rr Boost WTS



RIMS

Ã VALVE HOLE (MM): 6,5 :

1	V2314315	KIT FRONT/REAR RIM CROSSRIDE TUBELESS 29''
	V2190101	UST RIM STRIP 29x21c

SPOKES

2	V2381401	KIT 12 FT/RR BUTTED SPOKES 296mm MTB 29''
3	36689601	"KIT 12 DS CROSSROC/XRIDE UST/XMAX ELITE/XA ELITE 29"" SPK 2

HUB SHELLS

5	N/A	HUB BODY
6	M40076	HUB BEARINGS 17x30x7 6903 x 2
7	V2371201	KIT REAR QRM AXLE 135-142 / BOOST 148mm
8	35124501	SET OF 3 REAR AXLE/FREEWHEEL BODY SPACERS MTB L1
9	35126301	TS-2 FREEWHEEL BODY + SEAL 2013 (NO PAWLS) - while stock las
10	99610601	PAWLS KIT FOR ITS-4 (OR TS-2)
11	V2370401	KIT REAR AUTO ADJUSTING PLAY 12mm AXLE

Download date: 2024-07-16 / Update date: 2022-03-01

MAVIC Crossride Tubeless Quest 29

DELIVERED WITH

1 bottle of Mavic Sealant	
1 bottle of Mavic Sealant	
Tubeless rim tape	
UST valve and accessories	
Rear 12x142mm adapters	
User guide	
Rear 12x142mm adapters for ITS4 and TS2 (308 593 01 for ITS4, 329 650 01 for TS2) 1	
UST valve and accessories	
Tubeless rim tape	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to XD with optional driver body	
Front axle: convertible from 15mm thru axle to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- **Material :** S6000 Aluminum
- **Joint :** sleeved
- **Drilling :** traditional with H2 reinforcement
- **Valve hole diameter :** 8,5 mm with pop off reducer
- **Tyre :** UST Tubeless and tubetype
- **Material :** S6000 Aluminum
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C
- **ETRTO size 27.5" :** 584x21C
- **ETRTO size 29" :** 622x21C
- **ETRTO recommended tyre sizes :** 35mm to 69mm (1.4" to 2.7")
- **Joint :** sleeved
- **Drilling :** traditional with H2 reinforcement
- **Valve hole diameter :** 8,5 mm with pop off reducer
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C
- **ETRTO size 27.5" :** 584x21C
- **ETRTO size 29" :** 622x21C

SPOKES

- **Material :** steel
- **Shape :** straight pull, bladed, double butted
- **Nipples :** brass, ABS
- **Count :** 24 front and rear
- **Material :** steel
- **Lacing :** front and rear crossed 2
- **Shape :** straight pull, bladed, double butted
- **Nipples :** steel, ABS
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2

WHEEL HUB

- **Body :** aluminum
- **Axle material :** aluminum

Sealed cartridge bearings

- **Freewheel :** TS-2 alloy
- **Front and rear bodies :** aluminum

Shimano 11 speeds compatible
Sram XD Compatible (XX1-X01) with optionnal kit

- **Axle material :** aluminum

Sealed cartridge bearings

- **Freewheel :** TS-2 alloy

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)

WHEEL WEIGHTS

Wheel weight
Weight Rear 26": 965
Weight Rear 27.5": 995
Weight Rear 29": 1040

Downloaded on 2022-03-01 from Update date: 2022-03-01