


ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
Mindestgröße des Reifens: Breite 52mm - max. Druck 2.35Bar/34PSI
Recommended tire sizes: 50mm to 76mm (2.0" to 3.0")
Maximale Reifengröße: Breite 125mm - max. Druck 1.25Bar/18PSI
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 180kg, E-bike included

REFERENZEN RADDER



SPOKES

1	V00062531	Kit 16ft/rr Jbent bk rd spk275 27,5"+np
---	-----------	---

HUB SHELLS

	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
3	V2375501	Kit QRM auto front axle 100x12/15mm D6T
4	V2374001	KIT 12x100mm FRONT AXLE DCL QRM AUTO ALLROAD > 2019
5	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019
6	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL

ADAPTERS

7	V2680201	12mmFtRoadAxleAdaptersQRM
8	V2680501	12mm Road Axle Cap QRM Auto
9	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	V2680301	"Kit Ft Road Adapter 12 >> 9mm"
	99694101	2 REDUCERS 15/9mm

GELIEFERT MIT

Tubeless-Felgenband	
Kassettenunterlegscheibe M9 nicht am Hinterrad montiert	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo ED11, N3W and XD-R with optional driver bodies	
Front axle: 12mm thru axle, easily convertible to quick release with optional adapters. Convertible to 15mm with complete axle replacement	
Freilaufkörper: SRAM XD Straight-8-Konverter (Kit V2580101 separat erhältlich)	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters and axle replacement	
Freilaufkörper: SHIMANO HG light Straight-8-Konverter (Kit V3850101 separat erhältlich)	
Freilaufkörper: SHIMANO MS-Konverter (Kit V3990101 separat erhältlich)	
Front axle: 12mm thru axle, easily convertible to quick release with optional adapters. Convertible to 15mm with complete axle replacement	
Freilaufkörper: CAMPAGNOLO N3W-Konverter (Kit V4270101 separat erhältlich)	
ID360 Shimano Micro Spline alloy freewheel body (V3990101))	
Rear axle: 12mm thru axle, convertible to Quick Release with adapters (delivered with non-boost wheel)	
Instant Drive 360-Freilaufkörper für Sram XD-Ritzelkassetten (V3740101)	
HR-Achse: nur 1/4r Schraubmuttern (im Lieferumfang enthalten), M10x1-Gewinde	

Specifications

FELGEN

- Material : S6000 Aluminum
- Material : S6000 Aluminum
- Height : 21 mm
- Height : 21 mm
- Joint : sleeved
- Joint : sleeved
- Drilling : traditional
- Disc brake specific profile
- Internal width : 30 mm
- E-Bike specific rim profile
- Valve hole diameter : 6.5 mm
- Tire : UST Tubeless and tubetype
- Bohren : herkömmlich (vorne/hinten 32 Löcher)
- Internal width : 30 mm
- Disc brake specific profile
- E-Bike specific rim profile
- ETRTO-Größe : 584x30TSS
- Hookless profile
- ETRTO size 27.5" : 584x30TC
- Pinch Flat Protection sidewall (minimizes the risk of tire cuts and punctures)
- Reifen : UST Tubeless Ready - Verwendung mit Mavic Tubeless-Felgenband

RADNABE

- Körpermaterial : aluminium
- Front and rear bodies : aluminum
- Axle material : aluminum
- Körperdesign : CLASSIC
- Front : Quick release, 12x100 and 15x100 through axle compatible
- Standard Disc : 6 Löcher oder Center Lock®
- Rear : Quick Release, 12x142 and 12x135 compatible
- Axle material : aluminum
- Achsgröße : vorne 12x100 / hinten 12x142 - Mit den mitgelieferten Adaptern in einen Schnellspanner umwandelbar
- Freilauftechnologie : Instant Drive 360
- Freilauf : Shimano HG Straight-8
- Technologie der Lager : QRM automatische einstellung - abgedichtete patrone
- Nabe nur 1/4r Center-Lock®-Brems scheiben erhältlich
- Instant Drive 360 freewheel technology
- QRM Auto bearing preload technology

VERSIONS

RADGEWICHTE

1014