

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included Recommended tire sizes: 25 to 32 mm Max. Pressure: see indication on wheel and tire. If they differ, use the lowest of the 2

REFERENCES WHEELS

RIMS	OPTIONS	
&NBS	۶ ۳ ;:	V2373401
		ADAPTERS
1 V00063431	Kit Front/Rear rim Cosmic SLR32 Ltd	
		13 V3811001
SPOKES		V2510901
SI UKLS		V2510801
2 V4164801	Kit 12 CosmicSLR32 Disc aero sspk M6 291	
HUB SHELL	c	
NUD SNELL	5	
0 NI/A		

3	N/A	HUB BODY
3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V00046431	KIT AXE ID360 142LIGHT CL+CIR
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V00063631	Kit ID360 seal version 2 (larger)
8	V2251701	KIT ID360 2 RATCHETS + SPRING + GREASE
9	V2500501	KIT ID360 3 PADS NOISE REDUCING
10	V2251801	KIT 3 ID360 ROAD SPRINGS
11	V2580101	FREEHUB BODY XD Road ID360
11	V3430101	HG11 Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing

V2373401 KIT ID360 135/142 DCL L1 AXLE WITH CLIP

13	V3811001	KIT ROAD ID360 RR CL ENDCAP (12MM)
	V2510901	ID360 EVO RrAxleAdpt12x135/150
	V2510801	ID360 V2 RrAxleAdapt9x135



MAVIC COSMIC SLR 32 LTD

DELIVERED WITH

UST valve and accessories (129 838 01)		
User guide		

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo ED11, N3W and XD-R with optional driver bodies	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters and axle replacement	
Front axle: 12x100 thru axle, easily convertible to quick release with optional adapters. Not compatible with 15mm through axles	

Specifications

RIMS

• Material: 100% carbon fiber with UDÂ² external layer

• Material: 100% carbon fiber

-Height: 32mm Disc brake specific profile

• Tire : UST Tubeless and tubetype

- Internal width : 21 mm

• ETRTO size : 622x21TC Fore Carbon tapeless tubeless technology

UST tubeless technology

SPOKES

-Material : steel • Shape : straight pull, elliptical aero, double butted

(patented) • Nipples : Fore integrated aluminum

• Count: 24 front and rear

• Lacing : front and rear crossed 2, contactless

WHEEL HUB

Infinity hubs • Front and rear bodies : aluminum - Axle material : aluminum Instant Drive 360 freewheel technology QRM Auto bearing preload technology • Front : Quick release and 12x100 through axle compatible • Rear: Quick Release, 12x142 and 12x135 compatible

Hub available for Center Lock brake rotors only VERSIONS

- Disc standard : Center Lock® only • Freewheel : Shimano/Sram

WHEEL WEIGHTS

760