

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included Recommended tire sizes: 25 to 32 mm Max. Pressure: see indication on wheel and tire. If they differ, use the lowest of the 2

\$

## **REFERENCES WHEELS**

6



RI	MS	
	:	
1	V00063531	Kit Front/Rear rim Cosmic SL32 Ltd
	V2620101	UST RIM TAPE 25mm (for 21-24mm wide rim)
SP	OKES	
2	V4163401	Kit 12 Front/Rear Cosmic SL 32 Disc butted stainless spoke 2
HU	IB SHELLS	
3	N/A	HUB BODY
4	M40129	KIT 2 BEARINGS 6902 15x28x7
5	V2373301	KIT QRM AUTO FRONT AXLE 12mm > 2019
AD	<b>APTERS</b>	
6	V2680501	12mm Road Axle Cap QRM Auto
	V2680301	"Kit Ft Road Adapter 12 >> 9mm"



# MAVIC COSMIC SL 32 LTD

### **DELIVERED WITH**

Front QR adapters	
Rear QR adapters for Instant Drive 360 (B49 894 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	

## **COMPATIBILITY**

Freewheel: Shimano/Sram, convertible to Campagnolo ED11, N3W and XD-R with optional driver bodies	
Front axle: 12x100 thru axle, easily convertible to quick release with included adapters. Not compatible with 15mm through axles.	
Rear axle: 12mm thru axle, convertible to Quick Release with included adapters	

# **Specifications**

#### RIMS

• Material: 100% carbon fiber -Height: 32mm • Drilling : traditional Disc brake specific profile • Tire : UST Tubeless and tubetype . Internal width : 21 mm • ETRTO size : 622x21TC

UST tubeless technology

## SPOKES

- -Material : steel • Shape : straight pull, flat, double butted • Nipples : brass, ABS • Count : 24 front and rear
- Lacing : front and rear crossed 2, contactless

WHEEL HUB Infinity hubs • Front and rear bodies : aluminum -Axle material : aluminum Instant Drive 360 freewheel technology QRM Auto bearing preload technology • Front : Quick release and 12x100 through axle compatible • Rear: Quick Release, 12x142 and 12x135 compatible Hub available for Center Lock brake rotors only VERSIONS - Disc standard : Center Lock® only •Freewheel : Shimano/Sram

#### WHEEL WEIGHTS

692