

MAVIC COSMIC SL 45 DISC MAHLEX20

2023 FRONT

REFERENCES WHEELS

Maximum tyre pressure: 4.4bar/64PSI with a 28mm tyre - 2.6bar/38PSI with a 64mm tyre

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included

Maximum tyre size: width 62mm - pressure max. 3.8Bar/55PSI

MAVIC COSMIC SL 45 DISC MAHLEX20

2023 FRONT

DELIVERED WITH

Mavic tyre sealant (rear wheel) (355 466 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	

COMPATIBILITY

FTS-L Shimano / Sram freewheel body ([30871101] - Delivered on the wheel)	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9Ű. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	

Specifications

RIMS

• Material: 100% carbon fiber

■ Height: 45 mm

• Drilling: traditional (front/rear 28 holes)

Disc brake specific profile • ETRTO size: 622x19TC

- Tire : clincher

SPOKES

• Lacing: front radial, rear crossed 2

WHEEL HUB

-Body: aluminum Body design: INFINITY • Disc standard : 6 Bolts only WHEEL WEIGHTS