

MAVIC *DEEMAX DH 27.5*

ASTM CATEGORY 5 : GRAVITY RIDING FOCUSED ON THE DESCENT

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included

Minimum tyre size: width 52mm - pressure max. 2.95Bar/43PSI

REFERENCES WHEELS



DEEMAX DH 27.5

DELIVERED WITH

UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
User guide	
Specific disc bolts	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB aluminium (kit V3780101 sold separately)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separately)	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	
ID360 Shimano / Sram freewheel body ([V3430101] - Delivered on the wheel)	

Specifications

RIMS

- **Material** : Mxtal
 - **Height** : 22 mm
 - **Joint** : SUP welding technology
 - **Internal width** : 30 mm
 - **Drilling** : traditional (front/rear 28 holes)
- Disc brake specific profile
Asymmetrical rim design
- **ETRTO size 27.5"** : 584x30TC
 - **Tire** : clincher

SPOKES

- **Material** : steel
 - **Lacing** : front radial, rear crossed 2, contactless
- Isopulse lacing design

WHEEL HUB

- **Body** : aluminum
- **Disc standard** : 6 Bolts only
- **Axle material** : aluminum
- **Axle size** : rear 12x148 or 12x157
- **Axles** : Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Rear** : Quick Release, 12x142 and 12x135 compatible
- **Freewheel** : FTS-L steel

WHEEL WEIGHTS