

2024 REAR

## REFERENCES WHEELS

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included



2024 REAR

#### **DELIVERED WITH**

Pre-installed tubeless rim tape	
User guide	

### **COMPATIBILITY**

CONII ATIDILITI	
Freewheel body: convertible SRAM XD road (kit V2580101 sold separately)	
Freewheel body: convertible SHIMANO HG road (kit V3430101 sold separately)	
Freewheel body: convertible SHIMANO HG light road (kit V3850101 sold separately)	
Freewheel body: convertible SHIMANO MS (kit V3990101 sold separately)	
Freewheel body: convertible CAMPAGNOLO ED (kit V3440101 sold separately)	
Front axle: convertible from 15mm thru axle to Quick Release with included adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with adapters (delivered with non-boost wheel)	
FTS-L Shimano / Sram freewheel body ([30871101] - Delivered on the wheel)	

# **Specifications**

#### RIMS

Material: \$6000 Aluminum
 Height: 22 mm
 Joint: sleeved
 Internal width: 25 mm
 Drilling: traditional (front/rear 32 holes)

Disc brake specific profile
E-Bike specific rim profile
• ETRTO size 29": 622x25TSS

• Tire : clincher SPOKES

• Material : steel • Count : 20 front and rear

# WHEEL HUB

- Body: aluminum - Body design: CLASSIC - Axle material: aluminum

Axle size: front 12x100 / rear 12x142 Convertible to quick release with included adapters
 Axles: Front 15X110 (Boost) or 15x100; Rear

12X148 (Boost) or 12x142

• DH spacing axles: 12X150, 12x157,

12X157-7speed available

## WHEEL WEIGHTS