


REFERENCES WHEELS

R16701 Aksium One Rr



RIMS


VALVE HOLE $\varnothing$ (MM): 6.5 :

1 V2290915 KIT FRONT/REAR RIM AKSIUM ONE

SPOKES

2 V4160101 Kit 10 stainless spokes 285 Ft Ksyrium Equipe S/Ft & NDS Aks
2 10844901 KIT 10 FT KSYRIUM EQ S/FT+NDS AKSIUM SPK 285mm - while stock
3 10845001 KIT 10 DS AKSIUM STEEL AERO SPOKES 299mm

HUB SHELLS

4 N/A HUB BODY
5 M40660 REAR HUB 608+6001 BEARINGS
6 M40591 FTSL FREEWHEEL BODY ED10
7 M40592 FTSL FREEWHEEL BODY M10
8 M40067 INTERNAL FREEWHEEL SPACER FTSL/FTSX
9 99500001 FTSL/FTSX FREEHUB BODY SEAL
10 99603801 SHORT EXPENSIBLE BEARING SUPPORTS > 2008
11 99603901 REAR AXLE QRM ROAD 2008

MAVIC Aksium One

DELIVERED WITH

BR101 quick releases	
Rim tape	
User guide	

Specifications

RIMS

- **Material** : S6000 Aluminum
- **Height** : 24 mm
- **Joint** : pinned
- **Drilling** : traditional with H2 reinforcement
- **Brake track** : UB Control
- **Valve hole diameter** : 6.5 mm
- **Tyre** : clincher
- **ETRTO size** : 622x15C
- **Recommended tyre sizes** : 19 to 32 mm

SPOKES

- **Material** : steel
- **Shape** : straight pull, bladed
- **Nipples** : brass, ABS
- **Count** : 20 front and rear
- **Lacing** : radial front and rear non-drive side, crossed 2 rear drive side

WHEEL HUB

- **Front and rear bodies** : aluminum
- **Axle material** : steel
- Sealed cartridge bearings
- **Freewheel** : FTS-L steel

WHEEL WEIGHTS

Wheel weight 980