
MAVIC Cosmic Ultimate

ASTM CATEGORY 1 : road only
Recommended weight limit : 120kg

REFERENCES WHEELS

R57301	CosmicUlti16Rr



SPOKES

1	99603601	KIT 10 NIPPLES COSMIC CARBON ULTIMATE

HUB SHELLS

2	33000001	REAR HUB B9+6901 BEARINGS 2013
3	V2250801	KIT REAR AXLE COSMIC ULTIMATE
4	M40578	FTSL PAWLS KIT (ROAD WHEELS)
5	99500001	FTSL/FTSX FREEHUB BODY SEAL
6	30872801	SET OF 3 INTERNAL SILVER SPACERS 9mm FTS-L
7	30871201	FTS-L ROAD FREEWHEEL BODY ED11 8/9 compatible
7	30871101	FTS-L ROAD FREEWHEEL BODY HG11 8/9 compatible
9	99604501	SET OF 2 R.HUB RING COS.CARB.ULTIMATE

TYRES

10	37804625	Yksion ProPowerTub SSC

ADAPTERS

8	35117301	FT/RR FORK REST R-SYS/CC ULTIMATE > 2013/KSY PRO CARB T

Download date: 2024-03-29 / Update date: 2022-03-01

MAVIC Cosmic Ultimate

DELIVERED WITH

BR601 Titanium quick releases	
Carbon brake pads	
Multifonction adjustment wrench	
User guide	

Specifications

RIMS

- **Material :** 100% woven 12K carbon fiber
- **Height :** 40 mm
- **Drilling :** no holes, spokes molded to the rim
- **Brake track :** carbon with TgMAX technology
- **Valve hole diameter :** 6.5 mm
- **Tyre :** tubular
- **ETRTO size :** 28" tubular
- **Recommended tyre sizes :** 21 to 28 mm

SPOKES

- **Material :** unidirectional carbon fiber
- **Shape :** R2R
- **Nipples :** brass, ABS
- **Count :** 20 front and rear
- **Lacing :** crossed 2 front and rear drive side, radial non drive side

WHEEL HUB

- **Front body :** Front 100% carbon
- **Rear body :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

Wheel weight 665

Download date: 2024-03-29 / Update date: 2022-03-01