Cosmic Pro Carbon Exalith

ASTM CATEGORY 1 : road only
Recommended weight limit : 120kg

REFERENCES WHEELS

R57901	CosProCarbExalitRr



RIMS

VALVE HOLE Ã (MM): 6,5 :

1	V2404613	KIT REAR RIM COSMIC PRO CARBON EXALITH - while stock last
1	V4091713	KIT REAR RIM COSMIC CARBON SLE/COSMIC PRO CARBON EXALITH V s

SPOKES

2	32979201	10 BLK FR/NDRV SPOKES CC SLE CLINCHER 2013 288mm - while sto
2	32976801	KIT 10 AERO FT/NDS CXR 60 C BLK SPOKE 289mm
3	32979101	KIT 10 DS COSMIC CARB SLE C 13 BLK SPK 286mm

HUB SHELLS

4	N/A	HUB BODY
5	33000001	REAR HUB B9+6901 BEARINGS 2013
6	99500001	FTSL/FTSX FREEHUB BODY SEAL
7	30871101	FTS-L ROAD FREEWHEEL BODY HG11 8/9 compatible
7	30871201	FTS-L ROAD FREEWHEEL BODY ED11 8/9 compatible
8	30872801	SET OF 3 INTERNAL SILVER SPACERS 9mm FTS-L
9	M40578	FTSL PAWLS KIT (ROAD WHEELS)
10	V2250301	KIT REAR AXLE AERO HUB CXR/CC40/CC SLS/CC SLE/COSMIC PRO CAR
12	V2373101	KIT NUT FOR ROAD ALLOY THROUGH AXLE 9mm

ADAPTERS

11	35117301	FT/RR FORK REST R-SYS/CC ULTIMATE > 2013/KSY PRO CARB T

Download date: 2024-04-25 / Update date: 2022-03-01

MAVIC Cosmic Pro Carbon Exalith

DELIVERED WITH

BR601 quick releases	
Rim tape	
Exalith brake pads	
Multifonction adjustment wrench	
User guide	

Specifications

RIMS

- **Material :** Maxtal and 12K carbon fiber
- **Height :** 52 mm
- **Joint :** SUP
- **Drilling :** traditional
- **Brake track :** Exalith 2
- **Weight reduction :** ISM
- **Valve hole diameter :** 6.5 mm
- **Tyre :** clincher
- **ETRTO size :** 622x13C
- **Recommended tyre sizes :** 21 to 28 mm

SPOKES

- **Material :** steel
- **Shape :** straight pull, bladed, double butted
- **Nipples :** front aluminum, rear brass, ABS
- **Count :** front 16, rear 20
- **Lacing :** radial front and rear non-drive side, crossed 2 rear drive side

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** FTS-L steel

WHEEL WEIGHTS

Wheel weight 890

Download date: 2024-04-25 / Update date: 2022-03-01