



# Comète Road Tubular

参照ホイール

ASTM CATEGORY 1 : road only

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included

Recommended tyre sizes: 21 to 28 mm

Max. Pressure: 23mm 8.7 bars - 125 psi

23mm 8.7 bars - 125 psi  
25mm 9.0 bars - 130 psi  
28mm 9.5 bars - 138 psi

## 付属品

BR601 Quick Release	
Wheelbag	
BR601 Quick Release	
BR601 Quick Release	
BR601 Quick Release	
BR601 Quick Release	
BR601 Quick Release	
BR601 Quick Release	
Exalith brake pads	
Valve extender	
Exalith brake pads	
Exalith brake pads	
Exalith brake pads	
Exalith brake pads	
Exalith brake pads	
Exalith brake pads	
Multifonction adjustment wrench	
User guide	
Valve extender	
Valve extender	

## COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Freewheel: Shimano/Sram or Campagnolo, convertible to XD-R with optional driver body	
Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Front axle: Quick Release only	
Front axle: Quick Release only	
Front axle: Quick Release only	
Front axle: Quick Release only	
Front axle: Quick Release only	
Rear axle: Quick Release only	
Rear axle: Quick Release only	
Rear axle: Quick Release only	
Rear axle: Quick Release only	
Rear axle: Quick Release only	
Rear axle: Quick Release only	