

MAVIC Deemax

Recommended weight limit : 120kg
ETRTO recommended tyre sizes: 35mm to 69mm (1.4" to 2.7")

REFERENCES WHEELS

R67701	DmaxUlti16Rr 26 12x150





RIMS



VALVE HOLE Ã (MM): 6,5 :

1	99691913	KIT REAR RIM DEEMAX ULTIMATE YELLOW

SPOKES

2	30864001	KIT 16 NDS M7/7 DEEMAX ULTIMATE 12 SPK 268mm
3	30863901	KIT 16 DS M7/7 DEEMAX ULTIMATE 12 SPK 266mm

HUB SHELLS

4	N/A	HUB BODY
5	M40076	HUB BEARINGS 17x30x7 6903 x 2
6	35126001	ITS-4 FREEWHEEL BODY + SEAL 2013 (NO PAWLS)
7	99610701	ITS-4 FREEWHEEL SEAL
8	99610601	PAWLS KIT FOR ITS-4 (OR TS-2)
9	30870201	REAR AXLE KIT ITS4 150mm 2012

ADAPTERS

10	30872201	FRAME SUPPORT ITS-4 135mm REAR AXLE > 2012

Download date: 2024-03-29 / Update date: 2022-03-01

MAVIC Deemax

DELIVERED WITH

UST valve and accessories	
Rear QR adapters	
Multifonction adjustment wrench	
User guide	
12x157mm adaptors (308 593 01 for ITS4)	
UST valve and accessories	
Multifonction adjustment wrench	
User guide	
12x157mm adaptors (308 593 01 for ITS4)	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to XD with optional driver body	
Front axle: 20mm or 15mm thru axle with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- **Material :** Maxtal
- **Joint :** SUP
- **Drilling :** Fore

Disc brake specific profile

- **Weight reduction :** ISM with central spine
- **Valve hole diameter :** 6.5 mm
- **Material :** Maxtal
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C
- **ETRTO recommended tyre sizes :** 35mm to 69mm (1.4" to 2.7")
- **Joint :** SUP
- **Drilling :** Fore

Disc brake specific profile

- **Weight reduction :** ISM with central spine
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C

SPOKES

- **Material :** steel
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** front 28, rear 32
- **Material :** steel
- **Lacing :** front and rear crossed 3
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** front 28, rear 32
- **Lacing :** front and rear crossed 3

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

Shimano 11 speeds compatible

- **Front and rear bodies :** aluminum

Sram XD Compatible (XX1-X01) with optionnal kit

- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only

WHEEL WEIGHTS

Wheel weight
Weight Rear 26": 1055
Weight Rear 27.5": 1085

Download date: 2024-03-29 / Update date: 2022-03-01