
# Deemax Ultimate 27.5


2016
FRONT

ASTM CATEGORY 5 : extreme offroad
ETRTO recommended tyre sizes: 35mm to 69mm (1.4" to 2.7")

## REFERENCES WHEELS

| | |
|---|---|
| F41901 | DmaxUlti16 Ft27.5 |




## RIMS



**VALVE HOLE Ã (MM): 6.5 :**

| | | |
|---|---|---|
| 1 | V2312210 | "KIT FRONT RIM DEEMAX ULTIMATE 27,5"""" |

## SPOKES

| | | |
|---|---|---|
| 2 | V2380501 | "KIT 14 FRONT DEEMAX 27,5"" SPOKE 284mm" |

## HUB SHELLS

| | | |
|---|---|---|
| 3 | N/A | HUB BODY |
| 4 | M40179 | FRONT BEARING 25x37x7 20mm AXLE |
| 5 | 30870501 | FRONT AXLE 20mm CROSSMAX + DEEMAX ULTI 2012 |

## ADAPTERS

| | | |
|---|---|---|
| 6 | 12982901 | ADAPTER Ft 20x110mm |

Download date: 2024-03-29 / Update date: 2022-03-01

# MAVIC Deemax Ultimate 27.5

## DELIVERED WITH

| | |
|---|---|
| UST valve and accessories | |
| Front 20 mm adapters | |
| Rear QR adapters | |
| Multifonction adjustment wrench | |
| User guide | |
| Front 20 mm adapters | |
| 12x157mm adaptors (308 593 01 for ITS4) | |
| UST valve and accessories | |
| Multifonction adjustment wrench | |
| User guide | |
| 12x157mm adaptors (308 593 01 for ITS4) | |

## COMPATIBILITY

| | |
|---|---|
| Freewheel: Shimano/Sram, convertible to XD with optional driver body | |
| Front axle: 20mm or 15mm thru axle with optional adapters | |

## Specifications

### RIMS

- **Material :** Maxtal
- **Joint :** SUP
- **Drilling :** Fore

Disc brake specific profile

- **Weight reduction :** ISM with central spine
- **Valve hole diameter :** 6.5 mm
- **Material :** Maxtal
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C
- **ETRTO size 27.5" :** 584x21C
- **ETRTO recommended tyre sizes :** 35mm to 69mm (1.4" to 2.7")
- **Joint :** SUP
- **Drilling :** Fore

Disc brake specific profile

- **Weight reduction :** ISM with central spine
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 21 mm
- **ETRTO size 26" :** 559x21C

### SPOKES

- **Material :** steel
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** front 28, rear 32
- **Material :** steel
- **Lacing :** front and rear crossed 3

Downloaded: 2022-03-29 / Update date: 2022-03-01

### WHEEL HUB

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

Shimano 11 speeds compatible

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Sram XD Compatible (XX1-X01) with optionnal kit
Adjustable sealed cartridge bearings

- **Freewheel :** ITS-4 alloy

### VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only

### WHEEL WEIGHTS

Wheel weight
Weight Front 26": 910
Weight Front 27.5": 930