


For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included
Recommended tyre sizes: 25 to 52 mm
23mm 8.7 bars - 125 psi, 25mm 7.7 bars - 110 psi
Max. Pressure: 25mm 7.7 bars - 110 PSI

参照ホイール

R98821	CosProCarSiTDCLRr12x142	R78101	CosProCarbSLTDiscCLRr
--------	-------------------------	--------	-----------------------



RIMS



バルブ穴径 (MM) : 6,5 :

1	V2404013	KIT REART RIM COS PRO CARB SL DISC TUBULAR
---	----------	--

SPOKES

2	V2277301	KIT 12 DS COSMIC PRO CARB SL D T SPK 261mm - while stock las
2	V3663901	KIT 12 NON DRIVE SIDE BUTTED AERO STAINLESS SPOKE 261 +
3	V3663001	KIT 12 FRT/NDS COSMIC PRO CARB SL UST/UST Disc C/C Disc/T Di
3	V2277401	KIT 12 FT/NDS COSMIC PRO CARB SL D T 278mm SP - while stock

HUB SHELLS



4	N/A	HUB BODY
5	V2560201	KIT ID360 BEARINGS 15/28/7 + 17/28/7
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V2251601	ID360 SEAL + GREASE
8	V2500501	Kit 3 ID360 pad for noise reduction
9	V2251701	ID360 2 RATCHETS + SPRING + GREASE
10	V2251801	KIT 3 ID360 ROAD SPRINGS
11	V3430101	HG11 Freewheel Body ID360
12	V2252201	KIT 2 REAR HUB RETENTION RINGS 48mm
13	V2251501	3 ID360 WAVE WASHERS
14	V2251401	ID360 AXLE DISC CL
15	V2251101	KIT ID360 HUB THREADED CAP DISC CENTER LOCK

ADAPTERS

16	B4989901	Rear Axle Adapters 12/142 CL
----	----------	------------------------------

Cosmic Pro Carbon SL T Disc

付属品

BR601 quick releases	
Front 12 mm adapters	
Specific disc bolts	
User guide	
Front 12 mm adapters (B4104201) 1	
Rear 12x142mm adapters for Instant Drive 360 (B49 896 01 for ID360 6T, B49 899 01 for ID360 CL) 1	
Specific disc bolts	
Specific disc bolts	
Multifunction adjustment wrench (325 423 01) 1	
Multifunction adjustment wrench (325 423 01) 1	
User guide	
User guide	

COMPATIBILITY

1. Front axle: Shimano/Sram or Campagnolo, convertible to XD-R with optional driver body	
2. Front axle: convertible from 12mm thru axle to quick release or 15mm thru axle with optional adapters	
3. Front axle: convertible from 12mm thru axle to quick release or 15mm thru axle with optional adapters	
4. Rear axle: 12mm thru axle, convertible to Quick Release with optional adaptars	
5. Rear axle: 12mm thru axle, convertible to Quick Release with optional adaptars	

Specifications

リム

- Material : 3K carbon fibers
 - Height : 40 mm
 - Material : 3K carbon fibers
 - Material : 3K carbon fibers
 - Drilling : traditional
- Disc brake specific profile
- Valve hole diameter : 6.5 mm
 - Tyre : tubular
 - ETRTO size : 28" tubular
 - Recommended tyre sizes : 25 to 52 mm
 - Height : 40 mm
 - Height : 40 mm
 - Drilling : traditional
 - Drilling : traditional
- Disc brake specific profile
- Disc brake specific profile
- Valve hole diameter : 6.5 mm
 - Valve hole diameter : 6.5 mm
 - Tyre : tubular
 - Tyre : tubular
 - ETRTO size : 28" tubular
 - ETRTO size : 28" tubular

スポーク

- Material : steel
- Shape : straight pull, bladed, double butted
- Nipples : aluminum, ABS
- Count : 24 front and rear

ホイールハブ

- Front and rear bodies : aluminum
- Axle material : aluminum
- Sealed cartridge bearings
- Freewheel : Instant Drive 360
- Front and rear bodies : aluminum
- Front and rear bodies : aluminum
- Front : Quick release, 12 thru and 15 thru compatible
- Axle material : aluminum
- Axle material : aluminum
- Rear : 12x142 (convertible to quick release with optional adapters)
- Sealed cartridge bearings
- Freewheel : Instant Drive 360
- Freewheel : Instant Drive 360
- Front : Quick release, 12 thru and 15 thru compatible
- Rear : 12x142 (convertible to quick release with optional adapters)

VERSIONS

- Color : Black only
- Color : Black only
- Disc standard : Center Lock(R) only

ホイールの重み

- ホイール重量 (クイックリリースおよびクリンチャー/チューブラーを除く) (g) : 810