
2017
FRONT

MAVIC Aksium Disc TA

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
Recommended weight limit : 120kg
Recommended tire sizes: 25 to 32 mm

REFERENCES WHEELS

F68901	Aksium D6B TA Ft 12x100	F71631	AksDCLTA12mmFtWTS
F69001	Aksium DCL TA Ft 12x100		



RIMS



 :

1	V2290815	KIT FRT/REAR RIM AKSIUM ONE DISC/AKSIUM DISC

SPOKES

2	36690301	"KIT 12 FT/NDS XONE/XMAX - XA 29""/AKSIUM DISC 9 + 12 FT/AKS

HUB SHELLS

3	N/A	HUB BODY
4	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
5	V2371101	KIT FRONT QRM AXLE 100mm/BOOST 110mm
6	V2370301	KIT FRONT AUTO ADJUSTING PLAY 15mm AXLE

ADAPTERS

7	V2680201	12mmFtRoadAxleAdaptersQRM

Download date: 2024-03-28 / Update date: 2022-03-01

MAVIC Aksium Disc TA

DELIVERED WITH

BR101 quick releases (M40350 frt, M40351 rear road, M40352 rear MTB) 1	
Front 12 mm adapters (B4104201) 1	
Rear 12x142mm adapters for Instant Drive 360 (B49 896 01 for ID360 6T, B49 899 01 for ID360 CL) 1	
Rim tape	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Front axle: convertible from 12mm thru axle to quick release or 15mm thru axle with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- **Material :** S6000 Aluminum
- **Height :** 21 mm
- **Joint :** pinned
- **Drilling :** traditional with H2 reinforcement

Disc brake specific profile

- **Valve hole diameter :** 6.5 mm
- **Tire :** clincher
- **Internal width :** 17 mm
- **ETRTO size :** 622x17C

SPOKES

- **Material :** steel
- **Shape :** straight pull, round
- **Nipples :** steel, ABS
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Sealed cartridge bearings

- **Freewheel :** Instant Drive 360
- **Front :** Quick release, 12 thru and 15 thru compatible
- **Rear :** 12x142 (convertible to quick release with optional adapters)

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts or Center Lock(R)

WHEEL WEIGHTS

Wheel weight 905

Download date: 2024-03-28 / Update date: 2022-03-01