


ASTM CATEGORY 3 : offroad with jumps less than 61cm  
 Recommended weight limit : 120kg  
 Recommended tire sizes: 28 mm to 62 mm (1.1" to 2.5")  
 Recommended tyre sizes: 36 mm to 64 mm (1.4" to 2.5")

## REFERENCES WHEELS



## RIMS



Ø VALVE HOLE (MM): 6,5 :

|   |          |   |
|---|----------|---|
| 1 | V2317613 | KIT RR RIM CROSSMAX PRO 27,5" 22mm TSS OFFSET |
| 1 | V2316113 | KIT REAR RIM CROSSMAX PRO 27,5" 22mm TSS      |

## SPOKES

|   |          |  |
|---|----------|--|
| 2 | V2386401 | KIT 1 275mm 27,5" + 1 293mm 29" CROSSMAX PRO STAMPED BUTTE |
| 2 | V2384701 | KIT 12 FT/NDS CROSSMAX PRO 27,5" SPK 275mm                 |
| 3 | 36675101 | "KIT 10 DS XMAX SLR/END/PRO/DEEMAX PRO 27,5"" SPK 251,5mm" |

## HUB SHELLS

|    |          |   |
|----|----------|---|
| 4  | N/A      | HUB BODY                                    |
| 5  | M40076   | HUB BEARINGS 17x30x7 6903 x 2               |
| 6  | 99610701 | ITS-4 FREEWHEEL SEAL                        |
| 7  | 99610601 | PAWLS KIT FOR ITS-4 (OR TS-2)               |
| 8  | 35126001 | ITS-4 FREEWHEEL BODY + SEAL 2013 (NO PAWLS) |
| 9  | 35684101 | FREEHUB BODY XD TS2/ITS-4                   |
| 10 | 30870401 | REAR QRM + AXLE KIT ITS4 135mm from 2012    |
| 11 | 30871801 | ELASTIC RING 56mm diam. ITS-4 20 SPOKES     |
| 13 | N/A      | HUB BODY                                    |
| 14 | V2370801 | KIT REAR QRM+ AXLE BOOST ITS-4 148mm        |

## TYRES












|    |          |                |
|----|----------|----------------|
| 15 | 39243132 | Pulse Pro 27.5 |
| 15 | 39243121 | Pulse Pro 27.5 |

## ADAPTERS

|    |          |  |
|----|----------|--|
| 12 | 30872201 | FRAME SUPPORT ITS-4 135mm REAR AXLE > 2012 |
|    | 30873101 | 2 REAR REDUCERS 12/9,5mm 2012 ITS4 HUB     |

# MAVIC Crossmax Pro

## DELIVERED WITH

|   |   |
|---|---|
| 1 bottle of Mavic Sealant<br>(355 466 01)<br>1  |    |
| BX601 quick releases<br>(V24 503 01 frt, V24 504 01 rear)<br>1                            |    |
| BX601 quick releases<br>(V24 503 01 frt, V24 504 01 rear)<br>1                            |    |
| Front QR adapters<br>(996 941 01 for MTB or B41 043 01 for road)<br>1                     |    |
| Front QR adapters<br>(996 941 01 for MTB or B41 043 01 for road)<br>1                     |    |
| Rear QR adapters for ITS4 and TS2<br>(308 731 01)   |   |
| Rear 12x142mm adapters for ITS4 and TS2<br>(308 593 01 for ITS4, 329 650 01 for TS2)<br>1 |    |
| Rear 12x142mm adapters for ITS4 and TS2<br>(308 593 01 for ITS4, 329 650 01 for TS2)<br>1 |   |
| UST valve and accessories<br>(129 838 01)   |  |
| UST valve and accessories<br>(129 838 01)   |  |
| Multifunction adjustment wrench<br>(325 423 01)<br>1                                      |  |
| Multifunction adjustment wrench<br>(325 423 01)<br>1                                      |  |
| User guide  |   |
| User guide  |   |

## COMPATIBILITY

|   |  |
|---|--|
| Freewheel: Shimano/Sram, convertible to XD with optional driver body                |  |
| Freewheel: Shimano/Sram or XD   |  |
| Front axle: convertible from 15mm thru axle to Quick Release with included adapters |  |
| Front axle: convertible from 15mm thru axle to Quick Release with included adapters |  |
| Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters      |  |
| Rear axle: 12mm thru axle, convertible to Quick Release with included adapters      |  |

## Specifications

### RIMS

- Material : Mactal
- Material : Mactal
- Joint : SUP
- Joint : SUP
- Drilling : Fore
- Drilling : Fore
- Weight reduction : ISM 4D
- Weight reduction : ISM 4D
- Valve hole diameter : 6.5 mm
- Valve hole diameter : 6.5 mm
- Tire : UST Tubeless and tubetype
- Tire : UST Tubeless and tubetype
- Internal width : 22 mm
- Internal width : 22 mm
- ETRTO size 27.5" : 584x22ss

### WHEEL HUB

- Front and rear bodies : aluminum
- Front and rear bodies : aluminum
- Axle material : aluminum
- Axle material : aluminum
- Sealed cartridge bearings
- Sealed cartridge bearings
- Freewheel : ITS-4 alloy
- Freewheel : ITS-4 alloy

### VERSIONS

- Color : Black only
- Color : Black only
- Disc standard : 6 Bolts only
- Disc standard : 6 Bolts only
- Hub width : Boost (front 110, rear 148) or Non-

### WHEEL WEIGHTS

- Wheel weight
- Weight Rear 27.5": 835
- Weight Rear 29": 865