
Aksium Disc Allroad 650b

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
Recommended weight limit : 120kg
Recommended tire sizes: 25 to 32 mm
Max. Pressure: 30mm 5.8 bars - 85 PSI / 40mm 4.5 bars - 65 PSI

REFERENCES WHEELS

F71491	AksAlrdDCL650bFt QRx100 SV



RIMS



 :

1	V2730415	KIT FRONT/REAR RIM AKSIUM ALLROAD 650B

SPOKES

2	36690101	"KIT 12 FT/NDS CROSSONE/CROSSMAX/XA 27,5"" SPK 278mm"

HUB SHELLS



4	M40318	KIT 2 HUB BEARINGS 6001
5	99603701	FRONT AXLE QRM ROAD 2008
6	99603801	SHORT EXPENSIBLE BEARING SUPPORTS > 2008

Download date: 2024-03-29 / Update date: 2022-03-01

MAVIC Aksium Disc Allroad 650b

2017
FRONT

DELIVERED WITH

BR101 quick releases (M40350 frt, M40351 rear road, M40352 rear MTB) 1	
BR101 quick releases (M40350 frt, M40351 rear road, M40352 rear MTB) 1	
Rim tape	
Rim tape	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Front axle: Quick Release only	
Front axle: Quick Release only	
Rear axle: Quick Release only	
Rear axle: Quick Release only	

Specifications

RIMS

- **Material :** S6000 Aluminum
- **Material :** S6000 Aluminum
- **Height :** 21 mm
- **Height :** 21 mm
- **Joint :** pinned
- **Joint :** pinned
- **Drilling :** traditional with H2 reinforcement
- **Drilling :** traditional with H2 reinforcement

Disc brake specific profile
Disc brake specific profile

- **Valve hole diameter :** 6.5 mm
- **Valve hole diameter :** 6.5 mm
- **Tire :** clincher
- **Tire :** clincher
- **Internal width :** 19 mm
- **Internal width :** 19 mm
- **ETRTO size :** 584x19C
- **ETRTO size :** 584x19C

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** straight pull, round
- **Shape :** straight pull, round
- **Nipples :** steel, ABS
- **Nipples :** steel, ABS
- **Nipples :** brass, ABS
- **Count :** 24 front and rear
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2
- **Lacing :** front and rear crossed 2

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Axle material :** steel
- **Axle material :** steel

Sealed cartridge bearings

- **Front bearings :** sealed cartridge bearings (QRM), Rear bearings auto adjust sealed cartridge bearings (QRM Auto)
- **Freewheel :** FTS-L steel
- **Freewheel :** FTS-L steel

VERSIONS

- **Color :** Black only
- **Color :** Black only
- **Disc standard :** 6 Bolts or Center Lock(R)
- **Disc standard :** 6 Bolts or Center Lock(R)

WHEEL WEIGHTS

Wheel weight

Download date: 2024-03-29 / Update date: 2022-03-01