

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm


For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 120kg, bike included

Recommended tyre sizes: 25 to 32 mm

Max. Pressure: 23mm 8.7 bars - 125 psi, 25/28mm 7.7 bars - 110 psi

REFERENCES WHEELS

F73871 Aks18D6B Ft12x100SV F73881 Aks18DCLFt12x100SV





RIMS



:

1 V2290815 KIT FRT/REAR RIM AKSIUM ONE DISC/AKSIUM DISC

SPOKES

2 V2277201 KIT 12 FT 9/12 AKSIUM DISC ALLR 700 SPK 296mm

HUB SHELLS

4	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
5	V2371801	KIT FRONT AXLE 12mm L1 + WAVED WASHER + CLIP

OPTIONS

V2371901 KIT FRONT AXLE MTB L1 QRM AUTO 15x100mm

ADAPTERS

V2390801 KIT 2 FORK RESTS FRONT AXLE MTB QRM AUTO
V2680301 "Kit Ft Road Adapter 12 >> 9mm"

2018 FRONT

DELIVERED WITH

BR101 quick releases (M40350 frt, M40351 rear road, M40352 rear MTB)	
Rim tape	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Front axleÂ: 12mm thru axle. OptionalÂ: Easily convertible to quick release with adequate adapters, convertible to 15mm with complete axle replacement	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters (not available in Germany)	

Specifications

RIMS

Material: S6000 AluminumHeight: 21 mmJoint: pinned

• Drilling: traditional with H2 reinforcement

Disc brake specific profile

• Valve hole diameter: 6.5 mm

• Tyre : clincher

Internal width: 17 mmETRTO size: 622x17C

SPOKES

- Material : steel

Shape: straight pull, round
 Nipples: steel, ABS
 Count: 24 front and rear
 Lacing: front and rear crossed 2

WHEEL HUB

Front and rear bodies : aluminum

Avia material : aluminum

- Axle material : aluminum

• Front bearings: sealed cartridge bearings (QRM), Rear bearings auto adjust sealed cartridge bearings

(QRM Auto)

• Freewheel: Instant Drive 360

VERSIONS

-Color: Black only

• Disc standard: 6 Bolts or Center Lock(R)

WHEEL WEIGHTS

905